Xnightsbridge


DATASHEET



SFRLAT

230V LED Dimmable Reading Light with Dual USB A+A (5V DC 2.4A shared) - Anthracite

www.mlaccessories.co.uk



MLA PART CODE	SFRLAT
DESCRIPTION	230V LED Dimmable Reading Light with Dual USB A+A (5V DC 2.4A shared) - Anthracite
NET WEIGHT (KG)	0.302
FINISH	Anthracite
DIMENSIONS (MM)	Height - 87.5 Width - 87.5 Projection - 372 Recessed Depth - 20
MINIMUM MOUNTING BOX DEPTH	25-35mm (dependent on wiring conditions)
CONSTRUCTION	Construction - SPCC Steel
CLASS	I
IP RATING	IP20
WATTAGE (W)	2
LAMP TECHNOLOGY	LED
LUMENS (LM)	55
LUMENS LIGHT SOURCE ONLY (LM)	70
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	37.5
CIRCUIT WATTAGE (W)	1.9
ССТ	3000K
LIGHT COLOUR	Warm White
CRI	>80
RUNNING CURRENT (A)	0.019
SVM	0.03
PST-LM	<1
BEAM ANGLE (DEGREES)	120
L70B50 LIFESPAN (HRS)	30,000
DIMMABLE	Yes*
OPERATING TEMPERATURE	5~35°C
INPUT VOLTAGE	230V 50Hz





Xnightsbridge

TERMINAL CAPACITY	2 x 1.0mm² or 2 x 1.5mm²
NO. OF USB PORTS	2
NO. OF TYPE-A PORTS	2
USB CHARGING	5V DC 2.4A (shared)
DRIVER	EFFICIENCY FULL LOAD - 0.78
WARRANTY	2year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598, IEC 62368-1
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270871524

Date Created: 27/02/2025 18:11





