Xnightsbridge

DATASHEET



PM2000 10AX 1G 2-way Switch [Part M Compliant]

www.mlaccessories.co.uk

FINISH Anthracite Height - 86 Width - 86 Depth - 24.7 Projection - 11.3 Recessed Depth - 13.4 MINIMUM MOUNTING BOX DEPTH CONSTRUCTION CONSTRUCTION IP RATING IP20 INPUT VOLTAGE SWITCH TYPE Single Pole SWITCH FUNCTION CONDITION 2-Way LOAD/MAX. LOAD TERMINAL CAPACITY ANTI-MICROBIAL PROPERTIES MANUFACTURED IN ACCORDANCE WITH BS EN 60669-1	MLA PART CODE	PM2000
FINISH Anthracite Height - 86 Width - 86 Depth - 24.7 Projection - 11.3 Recessed Depth - 13.4 MINIMUM MOUNTING BOX DEPTH CONSTRUCTION CONSTRUCTION IP RATING IP20 INPUT VOLTAGE SWITCH TYPE Single Pole SWITCH FUNCTION CONDITION 2-Way LOAD/MAX. LOAD TERMINAL CAPACITY ANTI-MICROBIAL PROPERTIES MANUFACTURED IN ACCORDANCE WITH BS EN 60669-1	DESCRIPTION	10AX 1G 2-way Switch [Part M Compliant]
DIMENSIONS (MM) Height - 86 Width - 86 Depth - 24.7 Projection - 11.3 Recessed Depth - 13.4 MINIMUM MOUNTING BOX DEPTH CONSTRUCTION CONSTRUCTION IP RATING IP20 INPUT VOLTAGE SWITCH TYPE Single Pole SWITCH FUNCTION 2-Way LOAD/MAX. LOAD TERMINAL CAPACITY ANTI-MICROBIAL PROPERTIES MANUFACTURED IN ACCORDANCE WITH Height - 86 Width - 86 Depth - 24.7 Projection - 11.3 Recessed Depth - 13.4 Construction - Thermoset resin IP20 INPUT VOLTAGE Single Pole Single Pole Single Pole Switch Type Single Pole 3 Single Pole Switch Function 2-Way LOAD/MAX. LOAD 10AX TERMINAL CAPACITY 2 x 1.0mm² or 2 x 1.5mm² ANTI-MICROBIAL PROPERTIES BS EN 60669-1	NET WEIGHT (KG)	0.056
DIMENSIONS (MM) DIMENSIONS (MM) Dispit - 24.7 Projection - 11.3 Recessed Depth - 13.4 MINIMUM MOUNTING BOX DEPTH CONSTRUCTION Construction - Thermoset resin IP RATING IP20 INPUT VOLTAGE SWITCH TYPE Single Pole SWITCH FUNCTION 2-Way LOAD/MAX. LOAD TERMINAL CAPACITY ANTI-MICROBIAL PROPERTIES MANUFACTURED IN ACCORDANCE WITH BS EN 60669-1	FINISH	Anthracite
CONSTRUCTION IP RATING IP 20 INPUT VOLTAGE SWITCH TYPE Single Pole SWITCH FUNCTION LOAD/MAX. LOAD TERMINAL CAPACITY ANTI-MICROBIAL PROPERTIES MANUFACTURED IN ACCORDANCE WITH Construction - Thermoset resin IP 20 230V 50Hz Single Pole 2-Way 10AX 2 × 1.0mm² or 2 × 1.5mm² 3rd Party Tested to ISO 22196:2011 BS EN 60669-1	DIMENSIONS (MM)	Width - 86 Depth - 24.7 Projection - 11.3
IP RATING IP20 INPUT VOLTAGE 230V 50Hz SWITCH TYPE Single Pole SWITCH FUNCTION 2-Way LOAD/MAX. LOAD 10AX TERMINAL CAPACITY 2 x 1.0mm² or 2 x 1.5mm² ANTI-MICROBIAL PROPERTIES 3rd Party Tested to ISO 22196:2011 WARRANTY 25year(s) MANUFACTURED IN ACCORDANCE WITH BS EN 60669-1	MINIMUM MOUNTING BOX DEPTH	16mm
INPUT VOLTAGE SWITCH TYPE Single Pole SWITCH FUNCTION 2-Way LOAD/MAX. LOAD 10AX TERMINAL CAPACITY 2 x 1.0mm² or 2 x 1.5mm² ANTI-MICROBIAL PROPERTIES 3rd Party Tested to ISO 22196:2011 WARRANTY 25year(s) MANUFACTURED IN ACCORDANCE WITH BS EN 60669-1	CONSTRUCTION	Construction - Thermoset resin
SWITCH TYPE Single Pole SWITCH FUNCTION 2-Way LOAD/MAX. LOAD 10AX TERMINAL CAPACITY 2 x 1.0mm² or 2 x 1.5mm² ANTI-MICROBIAL PROPERTIES 3rd Party Tested to ISO 22196:2011 WARRANTY 25year(s) MANUFACTURED IN ACCORDANCE WITH BS EN 60669-1	IP RATING	IP20
SWITCH FUNCTION 2-Way LOAD/MAX. LOAD 10AX TERMINAL CAPACITY 2 x 1.0mm² or 2 x 1.5mm² ANTI-MICROBIAL PROPERTIES 3rd Party Tested to ISO 22196:2011 WARRANTY 25year(s) MANUFACTURED IN ACCORDANCE WITH BS EN 60669-1	INPUT VOLTAGE	230V 50Hz
LOAD/MAX. LOAD 10AX TERMINAL CAPACITY 2 x 1.0mm² or 2 x 1.5mm² ANTI-MICROBIAL PROPERTIES 3rd Party Tested to ISO 22196:2011 WARRANTY 25year(s) MANUFACTURED IN ACCORDANCE WITH BS EN 60669-1	SWITCH TYPE	Single Pole
TERMINAL CAPACITY 2 x 1.0mm² or 2 x 1.5mm² ANTI-MICROBIAL PROPERTIES 3rd Party Tested to ISO 22196:2011 WARRANTY 25year(s) MANUFACTURED IN ACCORDANCE WITH BS EN 60669-1	SWITCH FUNCTION	2-Way
ANTI-MICROBIAL PROPERTIES 3rd Party Tested to ISO 22196:2011 WARRANTY 25year(s) MANUFACTURED IN ACCORDANCE WITH BS EN 60669-1	LOAD/MAX. LOAD	10AX
WARRANTY 25year(s) MANUFACTURED IN ACCORDANCE WITH BS EN 60669-1	TERMINAL CAPACITY	2 x 1.0mm² or 2 x 1.5mm²
MANUFACTURED IN ACCORDANCE WITH BS EN 60669-1	ANTI-MICROBIAL PROPERTIES	3rd Party Tested to ISO 22196:2011
	WARRANTY	25year(s)
	MANUFACTURED IN ACCORDANCE WITH	BS EN 60669-1
ORIGIN OF MANUFACTURE China	ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE) Yes	DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN 5056270887556	EAN	5056270887556

Date Created: 27/02/2025 18:25





