Xnightsbridge

DATASHEET



SF82MNBN

45A DP Switch with Neon (2G size) - Black Nickel

www.mlaccessories.co.uk

| Description | MLA PART CODE | SF82MNBN |
|---|--|--|
| INISH Black Nickel Height - 147.5 Width - 87.5 Depth - 29.8 Projection - 9.3 Recessed Depth - 20.5 INIMIMUM MOUNTING BOX DEPTH ONSTRUCTION Construction - 201 Stainless steel LASS I PRATING IP20 IPUT VOLTAGE WITCH TYPE Double Pole ARTH TERMINAL Yes EON INDICATOR OAD/MAX. LOAD Height - 147.5 Width - 87.5 Depth - 29.8 Projection - 9.3 Recessed Depth - 20.5 I Construction - 201 Stainless steel 230V 50Hz Yes ARTH TERMINAL Yes OAD/MAX. LOAD | DESCRIPTION | 45A DP Switch with Neon (2G size) - Black Nickel |
| Height - 147.5 Width - 87.5 Depth - 29.8 Projection - 9.3 Recessed Depth - 20.5 IINIMUM MOUNTING BOX DEPTH ONSTRUCTION Construction - 201 Stainless steel LASS I PRATING IP20 IPUT VOLTAGE 230V 50Hz WITCH TYPE Double Pole ARTH TERMINAL Yes EON INDICATOR OAD/MAX. LOAD Height - 147.5 Width - 87.5 Depth - 29.8 Projection - 9.3 Recessed Depth - 20.5 IINIMUM MOUNTING BOX DEPTH 47mm Construction - 201 Stainless steel IP20 IP20 IP20 IP20 IP20 IP20 IP20 IP20 | NET WEIGHT (KG) | 0.25 |
| IMENSIONS (MM) Width - 87.5 Depth - 29.8 Projection - 9.3 Recessed Depth - 20.5 INNIMUM MOUNTING BOX DEPTH ONSTRUCTION Construction - 201 Stainless steel LASS I PRATING IP20 IPUT VOLTAGE WITCH TYPE Double Pole ARTH TERMINAL EON INDICATOR OAD/MAX. LOAD Width - 87.5 Depth - 29.8 Projection - 9.3 Recessed Depth - 20.5 IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII | FINISH | Black Nickel |
| ONSTRUCTION Construction - 201 Stainless steel I PRATING IP20 IPUT VOLTAGE WITCH TYPE Double Pole ARTH TERMINAL EON INDICATOR OAD/MAX. LOAD Construction - 201 Stainless steel I PRATING IP20 230V 50Hz Double Pole Yes 45A | DIMENSIONS (MM) | Width - 87.5 Depth - 29.8 Projection - 9.3 |
| I IP20 IP20 IPUT VOLTAGE 230V 50Hz WITCH TYPE Double Pole ARTH TERMINAL Yes EON INDICATOR Yes OAD/MAX. LOAD 45A | MINIMUM MOUNTING BOX DEPTH | 47mm |
| PRATING IP20 IPUT VOLTAGE 230V 50Hz WITCH TYPE Double Pole ARTH TERMINAL Yes EON INDICATOR Yes OAD/MAX. LOAD 45A | CONSTRUCTION | Construction - 201 Stainless steel |
| WITCH TYPE Double Pole ARTH TERMINAL Yes EON INDICATOR Yes OAD/MAX. LOAD 45A | CLASS | I |
| WITCH TYPE Double Pole ARTH TERMINAL Yes EON INDICATOR Yes OAD/MAX. LOAD 45A | IP RATING | IP20 |
| ARTH TERMINAL Yes EON INDICATOR Yes OAD/MAX. LOAD 45A | INPUT VOLTAGE | 230V 50Hz |
| EON INDICATOR Yes OAD/MAX. LOAD 45A | SWITCH TYPE | Double Pole |
| OAD/MAX. LOAD 45A | EARTH TERMINAL | Yes |
| | NEON INDICATOR | Yes |
| ERMINAL CAPACITY 2 x 6.0mm² or 3 x 4.0mm² | LOAD/MAX. LOAD | 45A |
| | TERMINAL CAPACITY | 2 x 6.0mm² or 3 x 4.0mm² |
| /ARRANTY 25year(s) | WARRANTY | 25year(s) |
| IANUFACTURED IN ACCORDANCE WITH BS EN 60669-1 | MANUFACTURED IN ACCORDANCE WITH | BS EN 60669-1 |
| RIGIN OF MANUFACTURE China | ORIGIN OF MANUFACTURE | China |
| ECLARATION OF CONFORMITY (HELD ON FILE) Yes | DECLARATION OF CONFORMITY (HELD ON FILE) | Yes |
| AN 5056270847734 | EAN | 5056270847734 |

Date Created: 27/02/2025 19:20





