


DATASHEET



LUMI6060PROAD

230V IP40 600 x 600mm CCT 30W LED 0-10V UGR19
Dimmable Backlit Panel

www.mlaccessories.co.uk



MLA PART CODE	LUMI6060PROAD
DESCRIPTION	230V IP40 600 x 600mm CCT 30W LED 0-10V UGR19 Dimmable Backlit Panel
NET WEIGHT (KG)	1.4
FINISH	White
DIFFUSER	Prismatic
DIMENSIONS (MM)	Length - 595 Height - 25 Width - 595 Projection - 9
CONSTRUCTION	Construction - Aluminium
CLASS	II
IP RATING	IP40
WATTAGE (W)	30
LAMP TECHNOLOGY	LED
LUMENS (LM)	3940/4100/3945
LUMENS LIGHT SOURCE ONLY (LM)	4530/4800/4800
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	160
CIRCUIT WATTAGE (W)	30.5
CCT	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.13
DISPLACEMENT FACTOR	>0.9
SVM	0.01
PST-LM	0.01
BEAM ANGLE (DEGREES)	90
L70B50 LIFESPAN (HRS)	50000
DIMMABLE	0-10V dimming only

EMERGENCY CONVERSION KIT	EMKIT2
IC RATED	No
DIFFUSER RATING	TP(a)
OPERATING TEMPERATURE	-10~40°C
INPUT VOLTAGE	230V 50Hz
WARRANTY	5year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270833683

Date Created: 27/02/2025 18:06

