## **X**nightsbridge

## **DATASHEET**



## **SF2194AT**

4G 2-way 10-200W (5-150W LED) Intelligent dimmer - Anthracite

www.mlaccessories.co.uk

DESCRIPTION  4G 2-way 10-200W (5-150W LED) Intelligent dimmer - Anthracite  NET WEIGHT (KG)  0.368  FINISH  Anthracite  Height - 87.5 Width - 147.5 Depth - 43.9 Projection - 22.6 Recessed Depth - 21.3  MINIMUM MOUNTING BOX DEPTH  CONSTRUCTION  CONSTRUCTION  CONSTRUCTION  CONSTRUCTION  IP RATING  IP RATING  IP RATING  INPUT VOLTAGE  SWITCH FUNCTION  2-Way  EARTH TERMINAL  Yes  LOAD/MAX. LOAD  10-200W (5-150W LED) Max. 15 Lamps per dimmer  TERMINAL TYPE  Screw
FINISH  Anthracite  Height - 87.5 Width - 147.5 Depth - 43.9 Projection - 22.6 Recessed Depth - 21.3  MINIMUM MOUNTING BOX DEPTH  CONSTRUCTION  CONSTRUCTION  CONSTRUCTION  IP RATING  IP RATING  INPUT VOLTAGE  SWITCH FUNCTION  2-Way  EARTH TERMINAL  Yes  LOAD/MAX. LOAD  Anthracite  Height - 87.5 Width - 147.5 Depth - 43.9 Projection - 22.6 Recessed Depth - 21.3  I Height - 87.5 Width - 147.5 Depth - 43.9 Projection - 22.6 Recessed Depth - 21.3  I Depth - 43.9 Projection - 22.6 Recessed Depth - 21.3  I Depth - 43.9 Projection - 22.6 Recessed Depth - 21.3  I Depth - 43.9 Projection - 22.6 Recessed Depth - 21.3  MINIMUM MOUNTING BOX DEPTH  25mm  Construction - SPCC Steel  I Depth - 43.9 Projection - 22.6 Recessed Depth - 21.3  I Depth - 43.9 Projection - 22.6 Recessed Depth - 21.3  I Depth - 43.9 Projection - 22.6 Recessed Depth - 21.3  I Depth - 43.9 Projection - 22.6 Recessed Depth - 21.3  I Depth - 43.9 Projection - 22.6 Recessed Depth - 21.3  I Depth - 43.9 Projection - 22.6 Recessed Depth - 21.3  I Depth - 43.9 Projection - 22.6 Recessed Depth - 21.3  I Depth - 43.9 Projection - 22.6 Recessed Depth - 21.3  I Depth - 43.9 Projection - 22.6 Recessed Depth - 21.3  I Depth - 43.9 Projection - 22.6 Recessed Depth - 21.3  I Depth - 43.9 Projection - 22.6 Recessed Depth - 21.3  I Depth - 43.9 Projection - 22.6 Recessed Depth - 21.3  I Depth - 43.9 Projection - 22.6 Recessed Depth - 21.3  I Depth - 43.9 Projection - 22.6 Recessed Depth - 21.3  I Depth - 43.9 Projection
DIMENSIONS (MM)  Height - 87.5 Width - 147.5 Depth - 43.9 Projection - 22.6 Recessed Depth - 21.3  MINIMUM MOUNTING BOX DEPTH  CONSTRUCTION  Construction - SPCC Steel  CLASS  I IP RATING  IP20 INPUT VOLTAGE  SWITCH FUNCTION  2-Way  EARTH TERMINAL  Yes  LOAD/MAX. LOAD  Height - 87.5 Width - 147.5 Depth - 43.9 Projection - 22.6 Recessed Depth - 21.3  MINIMUM MOUNTING BOX DEPTH  25mm  Construction - SPCC Steel  22mm  Construction - SPCC Steel  1 10-200W (5-150W LED) Max. 15 Lamps per dimmer
DIMENSIONS (MM)  Projection - 43.9 Projection - 22.6 Recessed Depth - 21.3  MINIMUM MOUNTING BOX DEPTH  CONSTRUCTION  CONSTRUCTION  CONSTRUCTION  CONSTRUCTION  IP RATING  IP20  INPUT VOLTAGE  SWITCH FUNCTION  2-Way  EARTH TERMINAL  Yes  LOAD/MAX. LOAD  Width - 147.5 Depth - 43.9 Projection - 22.6 Recessed Depth - 21.3  I Usually Seminary  Vesually Semin
CONSTRUCTION         Construction - SPCC Steel           CLASS         I           IP RATING         IP20           INPUT VOLTAGE         230V 50Hz           SWITCH FUNCTION         2-Way           EARTH TERMINAL         Yes           LOAD/MAX. LOAD         10-200W (5-150W LED) Max. 15 Lamps per dimmer
CLASS         I           IP RATING         IP20           INPUT VOLTAGE         230V 50Hz           SWITCH FUNCTION         2-Way           EARTH TERMINAL         Yes           LOAD/MAX. LOAD         10-200W (5-150W LED) Max. 15 Lamps per dimmer
IP RATING         IP20           INPUT VOLTAGE         230V 50Hz           SWITCH FUNCTION         2-Way           EARTH TERMINAL         Yes           LOAD/MAX. LOAD         10-200W (5-150W LED) Max. 15 Lamps per dimmer
INPUT VOLTAGE         230V 50Hz           SWITCH FUNCTION         2-Way           EARTH TERMINAL         Yes           LOAD/MAX. LOAD         10-200W (5-150W LED) Max. 15 Lamps per dimmer
SWITCH FUNCTION  2-Way  EARTH TERMINAL  Yes  LOAD/MAX. LOAD  10-200W (5-150W LED) Max. 15 Lamps per dimmer
EARTH TERMINAL Yes  LOAD/MAX. LOAD 10-200W (5-150W LED) Max. 15 Lamps per dimmer
LOAD/MAX. LOAD 10-200W (5-150W LED) Max. 15 Lamps per dimmer
, , , , , , , , , , , , , , , , , , , ,
TERMINAL TYPE Screw
TERMINAL CAPACITY 2 x 1.0mm² or 2 x 1.5mm²
BUILT-IN TECHNOLOGY Intelligent - Switchable Leading Edge and Trailing Edge (defau
ADDITIONAL FEATURES  Trim, switch modes and reset dimmer all from the front of the plate via the control knob
WARRANTY 2year(s)
ORIGIN OF MANUFACTURE China
DECLARATION OF CONFORMITY (HELD ON FILE)  Yes
EAN 5056270835458

Date Created: 28/02/2025 00:38



