Xnightsbridge

DATASHEET



BT20ACTDALIEM

230V IP65 20W CCT Adjustable DALI LED Emergency Bulkhead

www.mlaccessories.co.uk





MLA PART CODE	BT20ACTDALIEM
DESCRIPTION	230V IP65 20W CCT Adjustable DALI LED Emergency Bulkhead
NET WEIGHT (KG)	1.5
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Diameter - 380 Projection - 81
CONSTRUCTION	Construction - Polycarbonate
CLASS	II
IP RATING	IP65
IK RATING	IK08
WATTAGE (W)	20
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	1820/2070/2010
LUMENS LIGHT SOURCE ONLY (LM)	2580/2740/2665
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	138
LUMENS EMERGENCY MODE (LM)	165
CIRCUIT WATTAGE (W)	19.9
ССТ	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.090
DISPLACEMENT FACTOR	>0.9
SVM	0.017
PST-LM	0.027
BEAM ANGLE (DEGREES)	115





Xnightsbridge

L70B50 LIFESPAN (HRS)	50,000
LED COMPATIBLE	Yes
EMERGENCY	Maintained / Non-maintained / Switched
OPERATING TEMPERATURE	-20~45°C
INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	Blind grommet
BATTERY TYPE	LiFePO4
BATTERY INCLUDED	Yes
WARRANTY	5year(s)
WARRANTY INFORMATION	(excluding battery)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270844443

Date Created: 28/02/2025 01:01





