## **X**nightsbridge

## **DATASHEET**



## **AS20CWA**

ASHA 230V 20W IP54 CCT Adjustable LED Downlight

www.mlaccessories.co.uk





MLA PART CODE	AS20CWA
DESCRIPTION	ASHA 230V 20W IP54 CCT Adjustable LED Downlight
NET WEIGHT (KG)	0.635
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Diameter - 190 Base Diameter - 159 Recessed Depth - 46 Minimum Void - 96
CUT-OUT (MM)	Cut-out Diameter - 165
CONSTRUCTION	Construction - Polycarbonate Construction 2 - & aluminium
CLASS	II
IP RATING	IP54 (IP20 from above)
WATTAGE (W)	20
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	2215/2350/2385
LUMENS LIGHT SOURCE ONLY (LM)	2300/2550/2455
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	125
CIRCUIT WATTAGE (W)	20.13
ССТ	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.0911
DISPLACEMENT FACTOR	>0.9
SVM	0.006
PST-LM	0.168
BEAM ANGLE (DEGREES)	100





## **X**nightsbridge

LIFE SPAN (HRS)	50,000
L70B50 LIFESPAN (HRS)	45000
LED COMPATIBLE	Yes
DIMMABLE	No
EMERGENCY CONVERSION KIT	EMKIT2L
IC RATED	No
OPERATING TEMPERATURE	-20~40°C
INPUT VOLTAGE	230V 50Hz
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 23.55W OUTPUT VOLTAGE - 40V OUTPUT CURRENT - 588mA EFFICIENCY FULL LOAD - 87.46
WARRANTY	3year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270844337
D-1- 0	

Date Created: 28/02/2025 01:01





