



DATASHEET



WPCWA

230V IP65 2 x Wattage and 3 x CCT Adjustable LED Wall Pack with Photocell Sensor

www.mlaccessories.co.uk



MLA PART CODE	WPCWA
DESCRIPTION	230V IP65 2 x Wattage and 3 x CCT Adjustable LED Wall Pack with Photocell Sensor
NET WEIGHT (KG)	0.7
FINISH	Black
DIFFUSER	Prismatic
DIMENSIONS (MM)	Length - 74 Height - 218 Width - 147 Projection - 74
CONSTRUCTION	Construction - Polycarbonate Construction 2 - & aluminium
CLASS	II
IP RATING	IP65
IK RATING	IK10
WATTAGE (W)	10/15
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	1240/1300/1265, 1800/1950/1845
LUMENS LIGHT SOURCE ONLY (LM)	1525/1625/1560, 2160/2370/2190
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	140
CIRCUIT WATTAGE (W)	15.46
CCT	3000/4000/6500K
LIGHT COLOUR	CCT
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.07
SVM	0.008
PST-LM	0.121
BEAM ANGLE (DEGREES)	100

LIFE SPAN (HRS)	50,000
L70B50 LIFESPAN (HRS)	50,000
LED COMPATIBLE	Yes
DIMMABLE	No
OPERATING TEMPERATURE	-20~45°C
INPUT VOLTAGE	230V 50Hz
DRIVER	EFFICIENCY FULL LOAD - 92
SENSOR TYPE	Photocell
SENSOR LUX SETTINGS	On <30lx, Off >30lx
WARRANTY	5year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270846508

Date Created: 28/02/2025 01:04

