
Xnightsbridge

DATASHEET



CPL18CT 230V 18W CCT Adj Circular LED Panel- 217mm

www.mlaccessories.co.uk



MLA PART CODE	CPL18CT
DESCRIPTION	230V 18W CCT Adj Circular LED Panel- 217mm
NET WEIGHT (KG)	0.38
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Diameter - 217 Height - 15 Projection - 15 Base Diameter - 172 Recessed Depth - 0 Minimum Void - 50
CUT-OUT (MM)	Cut-out Diameter - 55 Min./Max. Cut-out - 55 - 175
CONSTRUCTION	Construction - Polycarbonate
CLASS	II
IP RATING	IP20
WATTAGE (W)	18
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	1300/1400/1360
LUMENS LIGHT SOURCE ONLY (LM)	2345
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	130
CIRCUIT WATTAGE (W)	18.1
ССТ	3000/4000/6000K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.089
DISPLACEMENT FACTOR	>0.9
SVM	0.17





Xnightsbridge

PST-LM	0.288
BEAM ANGLE (DEGREES)	120
LIFE SPAN (HRS)	30,000
L70B50 LIFESPAN (HRS)	30,000
DIMMABLE	No
IC RATED	Yes
OPERATING TEMPERATURE	-20~40°C
INPUT VOLTAGE	230V 50Hz
CABLE LENGTH (M)	0.3
WARRANTY	3year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832984092
D : 0 : 1 07/00/000F 10 07	

Date Created: 27/02/2025 12:07





