Xnightsbridge

DATASHEET



SN9002

13A 2G SP Switched Socket with Dual USB A+C (5V DC 4.8A shared) with Outboard Rockers

www.mlaccessories.co.uk

Shared With Outboard Rockers O.221	MLA PART CODE	SN9002
TINISH White Height - 86 Width - 146 Depth - 31.2 Projection - 13.1 Recessed Depth - 18.1 MINIMUM MOUNTING BOX DEPTH CONSTRUCTION CONSTRUCTION CONSTRUCTION CONSTRUCTION CONSTRUCTION P RATING IP20 NPUT VOLTAGE SWITCH TYPE Single Pole EARTH TERMINAL Yes LOAD/MAX. LOAD 13A TERMINAL CAPACITY NO. OF USB PORTS 1 Height - 86 Width - 146 Depth - 31.2 Projection - 13.1 Recessed Depth - 18.1 CONSTRUCTION CONSTRUCTION CONSTRUCTION CONSTRUCTION Terminal Yes 1 2 x 2.5mm² or 1 x 4.0mm² NO. OF TYPE-A PORTS 1	DESCRIPTION	13A 2G SP Switched Socket with Dual USB A+C (5V DC 4.8A shared) with Outboard Rockers
Height - 86 Width - 146 Depth - 31.2 Projection - 13.1 Recessed Depth - 18.1	NET WEIGHT (KG)	0.221
Width - 146 Depth - 31.2 Projection - 13.1 Recessed Depth - 18.1	FINISH	White
CONSTRUCTION Construction - Thermoset resin CLASS I P RATING IP20 NPUT VOLTAGE 230V 50Hz SWITCH TYPE Single Pole EARTH TERMINAL Yes LOAD/MAX. LOAD 13A TERMINAL CAPACITY 2 x 2.5mm² or 1 x 4.0mm² NO. OF USB PORTS 2 NO. OF TYPE-A PORTS 1	DIMENSIONS (MM)	Width - 146 Depth - 31.2 Projection - 13.1
CLASS	MINIMUM MOUNTING BOX DEPTH	25mm
PRATING	CONSTRUCTION	Construction - Thermoset resin
NPUT VOLTAGE 230V 50Hz SWITCH TYPE Single Pole EARTH TERMINAL Yes LOAD/MAX. LOAD 13A TERMINAL CAPACITY 2 x 2.5mm² or 1 x 4.0mm² NO. OF USB PORTS 2 NO. OF TYPE-A PORTS 1	CLASS	I
SWITCH TYPE Single Pole EARTH TERMINAL Yes .OAD/MAX. LOAD 13A TERMINAL CAPACITY 2 x 2.5mm² or 1 x 4.0mm² NO. OF USB PORTS 2 NO. OF TYPE-A PORTS 1	IP RATING	IP20
EARTH TERMINAL Yes .OAD/MAX. LOAD 13A TERMINAL CAPACITY 2 x 2.5mm² or 1 x 4.0mm² NO. OF USB PORTS 2 NO. OF TYPE-A PORTS 1	INPUT VOLTAGE	230V 50Hz
LOAD/MAX. LOAD 13A FERMINAL CAPACITY 2 x 2.5mm² or 1 x 4.0mm² NO. OF USB PORTS 2 NO. OF TYPE-A PORTS 1	SWITCH TYPE	Single Pole
TERMINAL CAPACITY 2 x 2.5mm² or 1 x 4.0mm² NO. OF USB PORTS 2 NO. OF TYPE-A PORTS 1	EARTH TERMINAL	Yes
NO. OF USB PORTS 2 NO. OF TYPE-A PORTS 1	LOAD/MAX. LOAD	13A
NO. OF TYPE-A PORTS	TERMINAL CAPACITY	2 x 2.5mm² or 1 x 4.0mm²
	NO. OF USB PORTS	2
IO. OF TYPE-C PORTS	NO. OF TYPE-A PORTS	1
	NO. OF TYPE-C PORTS	1
JSB CHARGING 5V DC 4.8A (shared)	USB CHARGING	5V DC 4.8A (shared)
ANTI-MICROBIAL PROPERTIES 3rd Party Tested to ISO 22196:2011	ANTI-MICROBIAL PROPERTIES	3rd Party Tested to ISO 22196:2011
WARRANTY 2year(s)	WARRANTY	2year(s)
DRIGIN OF MANUFACTURE China	ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE) Yes	DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN 5056270823240	EAN	5056270823240

Date Created: 27/02/2025 16:36



