



DATASHEET



SA3040CAD

SARA 230V IP20 LED Recessed Tri-Wattage and CCT 0-10V Scoop Downlight - 30/ 35/ 40W

www.mlaccessories.co.uk



MLA PART CODE	SA3040CAD
DESCRIPTION	SARA 230V IP20 LED Recessed Tri-Wattage and CCT 0-10V Scoop Downlight - 30/ 35/ 40W
NET WEIGHT (KG)	1.54
FINISH	White
DIFFUSER	Clear
DIMENSIONS (MM)	Diameter - 190 Depth - 130 Projection - 130 Recessed Depth - 130 Minimum Void - 180
CUT-OUT (MM)	Cut-out Diameter - 170
TILT (DEGREES)	40
ROTATION (DEGREES)	350
CONSTRUCTION	Construction - Aluminium Construction 2 - & glass
CLASS	II
IP RATING	IP20
WATTAGE (W)	30 / 35 / 40
LAMP TECHNOLOGY	CoB LED
LAMP INCLUDED	Yes
LUMENS (LM)	3175/3505/3470, 3560/3940/3880, 3925/4415/4280
LUMENS LIGHT SOURCE ONLY (LM)	4975
LUMEN TOLERANCE	10%
EFFICACY (LM/W)	130
CIRCUIT WATTAGE (W)	38.14
CCT	3000/4000/5000K
LIGHT COLOUR	CCT
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.168

DISPLACEMENT FACTOR	>0.7
SVM	0.011
PST-LM	0.575
BEAM ANGLE (DEGREES)	38
L70B50 LIFESPAN (HRS)	50,000
LED COMPATIBLE	Yes
DIMMABLE	Yes*
EMERGENCY CONVERSION KIT	EMKIT2L
IC RATED	No
OPERATING TEMPERATURE	-25~45°C
INPUT VOLTAGE	230V 50Hz
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 40W OUTPUT VOLTAGE - 9-42V OUTPUT CURRENT - 1000mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 87 AMBIENT TEMPERATURE (Ta) - 45°C CASE TEMPERATURE (Tc) - 75°C
WARRANTY	5year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270845525

Date Created: 28/02/2025 00:56

