Xnightsbridge


DATASHEET



UCLCT4

230V 4W LED Linkable Striplight CCT Adjustable (277mm)

www.mlaccessories.co.uk



MLA PART CODE	UCLCT4
DESCRIPTION	230V 4W LED Linkable Striplight CCT Adjustable (277mm)
NET WEIGHT (KG)	0.187
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 277 Width - 22.8 Projection - 36
CONSTRUCTION	Construction - Polycarbonate
CLASS	II
IP RATING	IP20
WATTAGE (W)	4
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	350 / 390 / 370
LUMENS LIGHT SOURCE ONLY (LM)	395
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	106.2
CIRCUIT WATTAGE (W)	3.9
ССТ	3000/4000/6500K
LIGHT COLOUR	CCT
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.031
DISPLACEMENT FACTOR	>0.7
SVM	0.028
PST-LM	0.008
BEAM ANGLE (DEGREES)	140
LIFE SPAN (HRS)	30,000
L70B50 LIFESPAN (HRS)	54,000





Xnightsbridge

DIMMABLE	No
OPERATING TEMPERATURE	-10~40°C
INPUT VOLTAGE	230V 50Hz
WARRANTY	2year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832999560

Date Created: 27/02/2025 12:47





