Xnightsbridge

DATASHEET



AS15CWA

ASHA 230V 16W IP54 CCT Adjustable LED Downlight

www.mlaccessories.co.uk





MLA PART CODE	AS15CWA
DESCRIPTION	ASHA 230V 16W IP54 CCT Adjustable LED Downlight
NET WEIGHT (KG)	0.455
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Diameter - 145 Base Diameter - 119 Recessed Depth - 46 Minimum Void - 96
CUT-OUT (MM)	Cut-out Diameter - 125
CONSTRUCTION	Construction - Polycarbonate Construction 2 - & aluminium
CLASS	II
IP RATING	IP54 (IP20 from above)
WATTAGE (W)	16
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	1620/1755/1735
LUMENS LIGHT SOURCE ONLY (LM)	1740/1930/1820
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	120
CIRCUIT WATTAGE (W)	16.05
ССТ	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.0736
DISPLACEMENT FACTOR	>0.9
SVM	0.022
PST-LM	0.012
BEAM ANGLE (DEGREES)	100





Xnightsbridge

LIFE SPAN (HRS)	50,000
L70B50 LIFESPAN (HRS)	45000
LED COMPATIBLE	Yes
DIMMABLE	No
EMERGENCY CONVERSION KIT	EMKIT2L
IC RATED	No
OPERATING TEMPERATURE	-20~40°C
INPUT VOLTAGE	230V 50Hz
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 15.36W OUTPUT VOLTAGE - 40V OUTPUT CURRENT - 384mA EFFICIENCY FULL LOAD - 87.63
WARRANTY	3year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270844313
D : 0 : 1 00/00/000E 04 04	

Date Created: 28/02/2025 01:01





