Xnightsbridge


DATASHEET



TRLEDA151

110V IP65 5ft 26W Single LED Non-Corrosive - 4000K

www.mlaccessories.co.uk



MLA PART CODE	TRLEDA151
DESCRIPTION	110V IP65 5ft 26W Single LED Non-Corrosive - 4000K
NET WEIGHT (KG)	2
FINISH	Yellow
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1563 Height - 90 Width - 90
CONSTRUCTION	Construction - Polycarbonate
CLASS	I
IP RATING	IP65
WATTAGE (W)	26
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	3500
LUMENS LIGHT SOURCE ONLY (LM)	3900
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	155
CIRCUIT WATTAGE (W)	25.13
ССТ	4000K
LIGHT COLOUR	Cool White
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.0231
DISPLACEMENT FACTOR	>0.9
SVM	0.025
PST-LM	0.084
BEAM ANGLE (DEGREES)	140
L70B50 LIFESPAN (HRS)	50,000
LED COMPATIBLE	Yes





Xnightsbridge

DIMMABLE	No
OPERATING TEMPERATURE	-20~35°C
INPUT VOLTAGE	110/230V
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	Compression gland
DRIVER	DRIVER TYPE - Constant Current
WARRANTY	5year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270856361

Date Created: 28/02/2025 00:58





