Xnightsbridge

DATASHEET



CU9919D

13A 1G DP Switched Socket with Dual USB A+C (20V DC 1.1A) Max. 22W

www.mlaccessories.co.uk

NET WEIGHT (KG) 0.12	MLA PART CODE	CU9919D
FINISH DIMENSIONS (MM) DIMENSIONS (MM)	DESCRIPTION	13A 1G DP Switched Socket with Dual USB A+C (20V DC 1.1A) Max. 22W
DIMENSIONS (MM) Height - 86 Width - 86 Popth - 34.6 Projection - 11.4 Recessed Depth - 23.2 MINIMUM MOUNTING BOX DEPTH 25-35mm (dependent on wiring conditions) CONSTRUCTION IP20 INPUT VOLTAGE 230V 50Hz SWITCH TYPE Double Pole EARTH TERMINAL Yes LOAD/MAX. LOAD MAX. 22W FASTCHARGE TERMINAL TYPE Captive TERMINAL TYPE Captive TERMINAL CAPACITY 2 x 2.5mm² or 1 x 4.0mm² NO. OF USB PORTS 1 NO. OF TYPE-A PORTS 1 USB CHARGING ANTI-MICROBIAL PROPERTIES 3rd Party Tested to ISO 22196:2011 WARRANTY 2year(s) ORIGIN OF MANUFACTURE DECLARATION OF CONFORMITY (HELD ON FILE)	NET WEIGHT (KG)	0.12
DIMENSIONS (MM) Dimensions (MM) Dipth - 34.6 Projection - 11.4 Recessed Depth - 23.2 MINIMUM MOUNTING BOX DEPTH 25-35mm (dependent on wiring conditions) CONSTRUCTION Construction - Thermoset resin CLASS I IP RATING IP20 INPUT VOLTAGE SWITCH TYPE Double Pole EARTH TERMINAL Yes LOAD/MAX. LOAD Max. 22W FASTCHARGE TERMINAL TYPE Captive TERMINAL CAPACITY 2 x 2.5mm² or 1 x 4.0mm² NO. OF USB PORTS 2 NO. OF TYPE-A PORTS 1 NO. OF TYPE-C PORTS 1 USB CHARGING ANTI-MICROBIAL PROPERTIES 3rd Party Tested to ISO 22196:2011 WARRANTY ORIGIN OF MANUFACTURE China DECLARATION OF CONFORMITY (HELD ON FILE)	FINISH	White
CONSTRUCTION CLASS IPRATING IPP20 INPUT VOLTAGE SWITCH TYPE Double Pole EARTH TERMINAL LOAD/MAX. LOAD TERMINAL TYPE TERMINAL CAPACITY NO. OF TYPE-A PORTS NO. OF TYPE-C PORTS USB CHARGING ANTI-MICROBIAL PROPERTIES DOUBLE POINTS TERMINAL CAPACITY ANTI-MICROBIAL PROPERTIES DOUBLE POINTS TO TAYLOR OF TAYLOR OF TAYLOR OF THE MANUFACTURE TERMINAL CAPACITY TO THE MANUFACTURE Construction - Thermoset resin I P20 ANAL 220 FASTCHARGE Captive Taylor OF TAYL	DIMENSIONS (MM)	Width - 86 Depth - 34.6 Projection - 11.4
I IP RATING	MINIMUM MOUNTING BOX DEPTH	25-35mm (dependent on wiring conditions)
IP RATING	CONSTRUCTION	Construction - Thermoset resin
SWITCH TYPE	CLASS	I
SWITCH TYPE EARTH TERMINAL Yes LOAD/MAX. LOAD Max. 22W FASTCHARGE TERMINAL TYPE Captive TERMINAL CAPACITY YES NO. OF USB PORTS NO. OF TYPE-A PORTS NO. OF TYPE-C PORTS 1 USB CHARGING ANTI-MICROBIAL PROPERTIES ORIGIN OF MANUFACTURE DOUBle Pole Nax. 22W FASTCHARGE Captive 2 x 2.5mm² or 1 x 4.0mm² 2 x 2.5mm² or 1 x 4.0mm² 1 x 4.0mm² 2 x 2.5mm² or 1 x 4.0mm² 2 x 2.5mm² or 1 x 4.0mm² 2 x 2.5mm² or 1 x 4.0mm² 1 x 4.0mm² 2 x 2.5mm² or 1 x	IP RATING	IP20
EARTH TERMINAL LOAD/MAX. LOAD Max. 22W FASTCHARGE TERMINAL TYPE Captive TERMINAL CAPACITY 2 x 2.5mm² or 1 x 4.0mm² NO. OF USB PORTS 2 NO. OF TYPE-A PORTS 1 NO. OF TYPE-C PORTS 1 USB CHARGING ANTI-MICROBIAL PROPERTIES 3rd Party Tested to ISO 22196:2011 WARRANTY ORIGIN OF MANUFACTURE China DECLARATION OF CONFORMITY (HELD ON FILE)	INPUT VOLTAGE	230V 50Hz
LOAD/MAX. LOAD Max. 22W FASTCHARGE Captive TERMINAL CAPACITY NO. OF USB PORTS NO. OF TYPE-A PORTS NO. OF TYPE-C PORTS USB CHARGING ANTI-MICROBIAL PROPERTIES ORIGIN OF MANUFACTURE DECLARATION OF CONFORMITY (HELD ON FILE) Max. 22W FASTCHARGE Captive 2 x 2.5mm² or 1 x 4.0mm² 2 ve 2.5mm² or 1 x 4.0mm² 1 A. On Captive Captive Captive Captive Captive Captive Captive Captive Captive 2 x 2.5mm² or 1 x 4.0mm² 1 No. OF TYPE-A PORTS 1 Substituted 1 Substituted China China DECLARATION OF CONFORMITY (HELD ON FILE) Yes	SWITCH TYPE	Double Pole
TERMINAL TYPE Captive TERMINAL CAPACITY 2 x 2.5mm² or 1 x 4.0mm² NO. OF USB PORTS 2 NO. OF TYPE-A PORTS 1 NO. OF TYPE-C PORTS 1 USB CHARGING 20V DC 1.1A ANTI-MICROBIAL PROPERTIES 3rd Party Tested to ISO 22196:2011 WARRANTY 2year(s) ORIGIN OF MANUFACTURE China DECLARATION OF CONFORMITY (HELD ON FILE) Yes	EARTH TERMINAL	Yes
TERMINAL CAPACITY 2 x 2.5mm² or 1 x 4.0mm² NO. OF USB PORTS 2 NO. OF TYPE-A PORTS 1 NO. OF TYPE-C PORTS 1 USB CHARGING 20V DC 1.1A ANTI-MICROBIAL PROPERTIES 3rd Party Tested to ISO 22196:2011 WARRANTY 2year(s) ORIGIN OF MANUFACTURE China DECLARATION OF CONFORMITY (HELD ON FILE) Yes	LOAD/MAX. LOAD	Max. 22W FASTCHARGE
NO. OF USB PORTS NO. OF TYPE-A PORTS 1 NO. OF TYPE-C PORTS 1 USB CHARGING ANTI-MICROBIAL PROPERTIES 3rd Party Tested to ISO 22196:2011 WARRANTY 2year(s) ORIGIN OF MANUFACTURE China DECLARATION OF CONFORMITY (HELD ON FILE)	TERMINAL TYPE	Captive
NO. OF TYPE-A PORTS NO. OF TYPE-C PORTS USB CHARGING ANTI-MICROBIAL PROPERTIES WARRANTY ORIGIN OF MANUFACTURE DECLARATION OF CONFORMITY (HELD ON FILE) 1 20V DC 1.1A 20V DC 1.1A 3rd Party Tested to ISO 22196:2011 2year(s) China Yes	TERMINAL CAPACITY	2 x 2.5mm ² or 1 x 4.0mm ²
NO. OF TYPE-C PORTS USB CHARGING ANTI-MICROBIAL PROPERTIES WARRANTY ORIGIN OF MANUFACTURE DECLARATION OF CONFORMITY (HELD ON FILE) 1 20V DC 1.1A 20V DC 1.1A 210 Str Party Tested to ISO 22196:2011 229ear(s) 229ear(s) 230 China 240 Yes	NO. OF USB PORTS	2
USB CHARGING ANTI-MICROBIAL PROPERTIES 3rd Party Tested to ISO 22196:2011 WARRANTY 2year(s) ORIGIN OF MANUFACTURE DECLARATION OF CONFORMITY (HELD ON FILE) Yes	NO. OF TYPE-A PORTS	1
ANTI-MICROBIAL PROPERTIES 3rd Party Tested to ISO 22196:2011 2year(s) ORIGIN OF MANUFACTURE China DECLARATION OF CONFORMITY (HELD ON FILE) Yes	NO. OF TYPE-C PORTS	1
WARRANTY 2year(s) ORIGIN OF MANUFACTURE China DECLARATION OF CONFORMITY (HELD ON FILE) Yes	USB CHARGING	20V DC 1.1A
ORIGIN OF MANUFACTURE China DECLARATION OF CONFORMITY (HELD ON FILE) Yes	ANTI-MICROBIAL PROPERTIES	3rd Party Tested to ISO 22196:2011
DECLARATION OF CONFORMITY (HELD ON FILE) Yes	WARRANTY	2year(s)
	ORIGIN OF MANUFACTURE	China
EAN 5056270846867	DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
2-t- Over-to-di 00/00/0005 01:04	EAN	5056270846867

Date Created: 28/02/2025 01:04



