Xnightsbridge

DATASHEET



CU298MM

Multimedia Combination Plate

www.mlaccessories.co.uk

NET WEIGHT (KG) FINISH White Height - 175 Wicht - 295 Depth - 43.9 Projection - 24 Recessed Depth - 19.9 CUT-OUT (MM) CUT-OUT (MM) CUT-OUT (MM) CONSTRUCTION CONSTRUCTION IP RATING IP20 INPUT VOLTAGE SWITCH TYPE DOUBLE POILE LOAD/MAX. LOAD TERMINAL TYPE SCREW TERMINAL TYPE ADDITIONAL FEATURES ANTI-MICROBIAL PROPERTIES ANTI-MICROBIAL PROPERTIES TO MANUFACTURED IN ACCORDANCE WITH WARRANTY MANUFACTURED IN ACCORDANCE WITH BS 1363-2 ORIGIN OF MANUFACTURE CUT-OUT White Height - 175 Wicht - 295 Dothe Cut-out Box W/H/D - 282x162x48 ATM CONSTRUCTION - 24 Recessed Depth - 19.9 Cut-out Box W/H/D - 282x162x48 MAINIMUM MOUNTING BOX DEPTH Construction - Thermoset resin IP20 IP20	MLA PART CODE	CU298MM
FINISH DIMENSIONS (MM) DIMENSIONS (MM) DIMENSIONS (MM) DIMENSIONS (MM) DIMENSIONS (MM) CUT-OUT (MM) CONSTRUCTION CONSTRU	DESCRIPTION	Multimedia Combination Plate
DIMENSIONS (MM) DIMENSIONS (MM) DIMENSIONS (MM) DIMENSIONS (MM) DIMENSIONS (MM) CUT-OUT (MM) C	NET WEIGHT (KG)	0.473
DIMENSIONS (MM) Dimensions (MM) Cut-out (MM) Cut-out Box W/H/D - 282x162x48 MINIMUM MOUNTING BOX DEPTH CONSTRUCTION IP RATING IP20 INPUT VOLTAGE SWITCH TYPE Double Pole LOAD/MAX. LOAD TERMINAL TYPE TERMINAL CAPACITY ADDITIONAL FEATURES ANTI-MICROBIAL PROPERTIES ANTI-MICROBIAL PROPERTIES MANUFACTURED IN ACCORDANCE WITH BS 1363-2 ORIGIN OF MANUFACTURE	FINISH	White
MINIMUM MOUNTING BOX DEPTH CONSTRUCTION Construction - Thermoset resin IP20 INPUT VOLTAGE SWITCH TYPE Double Pole LOAD/MAX. LOAD TERMINAL TYPE SCREW TERMINAL CAPACITY ADDITIONAL FEATURES ANTI-MICROBIAL PROPERTIES MANUFACTURED IN ACCORDANCE WITH DOUBLE 47mm Construction - Thermoset resin IP20 1P20 1P20 1P20 1P20 1P20 1P20 1P20 1P20 1P20 2 x 23V 50Hz 2 x 13A 2 x 13A TERMINAL CAPACITY 2 x 2.5mm² or 1 x 4.0mm² 2 x 2.5mm² or 1 x 4.0mm² 2 x 2G Switched Sockets + 2 x 4G Modular positions ANTI-MICROBIAL PROPERTIES 3rd Party Tested to ISO 22196:2011 FUNCTION Lounge Plate / Combination Plate WARRANTY 25year(s) MANUFACTURED IN ACCORDANCE WITH BS 1363-2 ORIGIN OF MANUFACTURE	DIMENSIONS (MM)	Width - 295 Depth - 43.9 Projection - 24
CONSTRUCTION IP RATING IP20 INPUT VOLTAGE SWITCH TYPE LOAD/MAX. LOAD TERMINAL TYPE TERMINAL TYPE TERMINAL CAPACITY ADDITIONAL FEATURES ANTI-MICROBIAL PROPERTIES TENDER TO SUBJECT OF MANUFACTURE WARRANTY Construction - Thermoset resin IP20 Double Pole 230V 50Hz Screw TERMINAL CAPACITY Screw 2 x 2.5mm² or 1 x 4.0mm² 2 x 2.5mm² or 1 x 4.0mm² 2 x 2G Switched Sockets + 2 x 4G Modular positions 3rd Party Tested to ISO 22196:2011 Lounge Plate / Combination Plate WARRANTY 25year(s) MANUFACTURED IN ACCORDANCE WITH BS 1363-2 ORIGIN OF MANUFACTURE	CUT-OUT (MM)	Cut-out Box W/H/D - 282x162x48
IP RATING INPUT VOLTAGE SWITCH TYPE Double Pole LOAD/MAX. LOAD 2 x 13A TERMINAL TYPE Screw TERMINAL CAPACITY 2 x 2.5mm² or 1 x 4.0mm² ADDITIONAL FEATURES 2 x 2G Switched Sockets + 2 x 4G Modular positions ANTI-MICROBIAL PROPERTIES 3rd Party Tested to ISO 22196:2011 FUNCTION Lounge Plate / Combination Plate WARRANTY 25year(s) MANUFACTURED IN ACCORDANCE WITH BS 1363-2 ORIGIN OF MANUFACTURE China	MINIMUM MOUNTING BOX DEPTH	47mm
INPUT VOLTAGE SWITCH TYPE Double Pole LOAD/MAX. LOAD 2 x 13A TERMINAL TYPE Screw TERMINAL CAPACITY ADDITIONAL FEATURES ANTI-MICROBIAL PROPERTIES FUNCTION WARRANTY WARRANTY MANUFACTURED IN ACCORDANCE WITH Double Pole 2 x 13A 2 x 2.5mm² or 1 x 4.0mm² 2 x 2.5mm² or 1 x 4.0mm² 2 x 2G Switched Sockets + 2 x 4G Modular positions 3rd Party Tested to ISO 22196:2011 Lounge Plate / Combination Plate WARRANTY 25year(s) MANUFACTURED IN ACCORDANCE WITH BS 1363-2 China	CONSTRUCTION	Construction - Thermoset resin
SWITCH TYPE LOAD/MAX. LOAD 2 x 13A TERMINAL TYPE SCREW TERMINAL CAPACITY ADDITIONAL FEATURES ANTI-MICROBIAL PROPERTIES FUNCTION WARRANTY MANUFACTURED IN ACCORDANCE WITH Double Pole 2 x 13A SCREW 2 x 2.5mm² or 1 x 4.0mm² 2 x 2.5mm² or 1 x 4.0mm² 2 x 2G Switched Sockets + 2 x 4G Modular positions 3rd Party Tested to ISO 22196:2011 Lounge Plate / Combination Plate WARRANTY BS 1363-2 ORIGIN OF MANUFACTURE China	IP RATING	IP20
LOAD/MAX. LOAD TERMINAL TYPE Screw TERMINAL CAPACITY ADDITIONAL FEATURES ANTI-MICROBIAL PROPERTIES SIRP Party Tested to ISO 22196:2011 FUNCTION Lounge Plate / Combination Plate WARRANTY 25year(s) MANUFACTURED IN ACCORDANCE WITH BS 1363-2 ORIGIN OF MANUFACTURE China	INPUT VOLTAGE	230V 50Hz
TERMINAL TYPE TERMINAL CAPACITY ADDITIONAL FEATURES ANTI-MICROBIAL PROPERTIES FUNCTION FUNCTION Capacity Capacity Combination Plate WARRANTY Consider the second of the second	SWITCH TYPE	Double Pole
TERMINAL CAPACITY 2 x 2.5mm² or 1 x 4.0mm² 2 x 2G Switched Sockets + 2 x 4G Modular positions ANTI-MICROBIAL PROPERTIES 3rd Party Tested to ISO 22196:2011 FUNCTION Lounge Plate / Combination Plate WARRANTY 25year(s) MANUFACTURED IN ACCORDANCE WITH BS 1363-2 China	LOAD/MAX. LOAD	2 x 13A
ADDITIONAL FEATURES 2 x 2G Switched Sockets + 2 x 4G Modular positions 3rd Party Tested to ISO 22196:2011 FUNCTION Lounge Plate / Combination Plate WARRANTY 25year(s) MANUFACTURED IN ACCORDANCE WITH BS 1363-2 China	TERMINAL TYPE	Screw
ANTI-MICROBIAL PROPERTIES 3rd Party Tested to ISO 22196:2011 Lounge Plate / Combination Plate WARRANTY 25year(s) MANUFACTURED IN ACCORDANCE WITH BS 1363-2 ORIGIN OF MANUFACTURE China	TERMINAL CAPACITY	2 x 2.5mm² or 1 x 4.0mm²
FUNCTION Lounge Plate / Combination Plate WARRANTY 25year(s) MANUFACTURED IN ACCORDANCE WITH BS 1363-2 ORIGIN OF MANUFACTURE China	ADDITIONAL FEATURES	2 x 2G Switched Sockets + 2 x 4G Modular positions
WARRANTY 25year(s) MANUFACTURED IN ACCORDANCE WITH BS 1363-2 ORIGIN OF MANUFACTURE China	ANTI-MICROBIAL PROPERTIES	3rd Party Tested to ISO 22196:2011
MANUFACTURED IN ACCORDANCE WITH ORIGIN OF MANUFACTURE China	FUNCTION	Lounge Plate / Combination Plate
ORIGIN OF MANUFACTURE China	WARRANTY	25year(s)
	MANUFACTURED IN ACCORDANCE WITH	BS 1363-2
DECLARATION OF CONFORMITY (HELD ON FILE) Yes	ORIGIN OF MANUFACTURE	China
	DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN 5056270806595		5056270806595

Date Created: 27/02/2025 15:29



