Xnightsbridge


DATASHEET



TNXT

TENAX 230V Wattage and CCT Adjustable LED Gear Tray

www.mlaccessories.co.uk



MLA PART CODE	TNXT
DESCRIPTION	TENAX 230V Wattage and CCT Adjustable LED Gear Tray
NET WEIGHT (KG)	0.225
DIMENSIONS (MM)	Length - 235 Width - 235 Projection - 28
CONSTRUCTION	Construction - Aluminium
CLASS	II
IP RATING	IP20
WATTAGE (W)	10/15/20
LAMP TECHNOLOGY	SMD LED
LUMENS (LM)	1360/1480/1405, 1905/2090/1960, 2345/2630/2415
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	151/147/141
CIRCUIT WATTAGE (W)	9.7/14.3/18.6
ССТ	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.049/0.067/0.085
DISPLACEMENT FACTOR	>0.7
SVM	0.69
PST-LM	0.36
BEAM ANGLE (DEGREES)	120
L70B50 LIFESPAN (HRS)	40,000
DIMMABLE	No
OPERATING TEMPERATURE	-20~35°C
INPUT VOLTAGE	230V 50Hz





Xnightsbridge

DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 18W OUTPUT CURRENT - 360mA POWER FACTOR - 0.96 EFFICIENCY FULL LOAD - 0.89 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20~50°C CASE TEMPERATURE (Tc) - 85°C
WARRANTY	5year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270876796

Date Created: 27/02/2025 19:48





