Xnightsbridge

DATASHEET



FP1100BB 10A Fan Isolator Switch - Brushed Brass

www.mlaccessories.co.uk

DESCRIPTION10A Fan Isolator Switch - Brushed BrassNET WEIGHT (KG)0.09FINISHBrushed BrassDIMENSIONS (MM)Height - 87.5 Width - 87.5 Depth - 21.6 Projection - 6.8 Recessed Depth - 14.8MINIMUM MOUNTING BOX DEPTH16mmCONSTRUCTIONConstruction - 201 Stainless steelIP RATINGIP20INPUT VOLTAGE230V 50HzSWITCH FUNCTIONFan IsolatorEARTH TERMINALYes	ILA PART CODE	FP1100BB
FINISH Brushed Brass Height - 87.5 Width - 87.5 Width - 87.5 Depth - 21.6 Projection - 6.8 Recessed Depth - 14.8 MINIMUM MOUNTING BOX DEPTH CONSTRUCTION CONSTRUCTION IP RATING IP 20 INPUT VOLTAGE SWITCH FUNCTION EARTH TERMINAL Brushed Brass Height - 87.5 Width - 87.5 Depth - 21.6 Projection - 6.8 Recessed Depth - 14.8 I 6mm Construction - 201 Stainless steel IP RATING IP 20 INPUT VOLTAGE SWITCH FUNCTION Fan Isolator EARTH TERMINAL	ESCRIPTION	10A Fan Isolator Switch - Brushed Brass
DIMENSIONS (MM) Height - 87.5 Width - 87.5 Depth - 21.6 Projection - 6.8 Recessed Depth - 14.8 MINIMUM MOUNTING BOX DEPTH 16mm CONSTRUCTION Construction - 201 Stainless steel IP RATING IP20 INPUT VOLTAGE 230V 50Hz SWITCH FUNCTION Fan Isolator EARTH TERMINAL Yes	IET WEIGHT (KG)	0.09
DIMENSIONS (MM) Width - 87.5 Depth - 21.6 Projection - 6.8 Recessed Depth - 14.8 MINIMUM MOUNTING BOX DEPTH CONSTRUCTION Construction - 201 Stainless steel IP RATING IP20 INPUT VOLTAGE SWITCH FUNCTION EARTH TERMINAL Width - 87.5 Depth - 21.6 Projection - 6.8 Recessed Depth - 14.8 Construction - 201 Stainless steel IP20 IP20 INPUT VOLTAGE Yes	INISH	Brushed Brass
CONSTRUCTION IP RATING IP20 INPUT VOLTAGE SWITCH FUNCTION EARTH TERMINAL Construction - 201 Stainless steel IP20 Fan Isolator Yes	DIMENSIONS (MM)	Width - 87.5 Depth - 21.6 Projection - 6.8
IP RATING IP20 INPUT VOLTAGE 230V 50Hz SWITCH FUNCTION Fan Isolator EARTH TERMINAL Yes	IINIMUM MOUNTING BOX DEPTH	16mm
INPUT VOLTAGE SWITCH FUNCTION EARTH TERMINAL 230V 50Hz Fan Isolator Yes	ONSTRUCTION	Construction - 201 Stainless steel
SWITCH FUNCTION Fan Isolator EARTH TERMINAL Yes	PRATING	IP20
EARTH TERMINAL Yes	NPUT VOLTAGE	230V 50Hz
	WITCH FUNCTION	Fan Isolator
	ARTH TERMINAL	Yes
LOAD/MAX. LOAD 10A	OAD/MAX. LOAD	10A
TERMINAL CAPACITY 2 x 1.0mm² or 2 x 1.5mm²	ERMINAL CAPACITY	2 x 1.0mm ² or 2 x 1.5mm ²
ADDITIONAL FEATURES Triple Pole	DDITIONAL FEATURES	Triple Pole
WARRANTY 25year(s)	VARRANTY	25year(s)
MANUFACTURED IN ACCORDANCE WITH BS EN 60669-1, BS EN 60669-2-4	IANUFACTURED IN ACCORDANCE WITH	BS EN 60669-1, BS EN 60669-2-4
ORIGIN OF MANUFACTURE China	RIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE) Yes	ECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN 5055832916826	AN	5055832916826

Date Created: 27/02/2025 09:15





