Xnightsbridge


DATASHEET



SHE2GP

230V IP65 18W LED Eyelid Bulkhead CCT with Daylight Sensor Grey

www.mlaccessories.co.uk



| MLA PART CODE | SHE2GP |
|-------------------------------|---|
| DESCRIPTION | 230V IP65 18W LED Eyelid Bulkhead CCT with Daylight Sensor Grey |
| NET WEIGHT (KG) | 2.475 |
| FINISH | Grey |
| DIFFUSER | Opal |
| DIMENSIONS (MM) | Diameter - 360 Projection - 94 |
| CONSTRUCTION | Construction - Die-cast aluminium |
| CLASS | l . |
| IP RATING | IP65 |
| IK RATING | IK10 |
| WATTAGE (W) | 18 |
| LAMP TECHNOLOGY | SMD LED |
| LUMENS (LM) | 1020/1080/1090 |
| LUMENS LIGHT SOURCE ONLY (LM) | 3000 |
| LUMEN TOLERANCE | 5% |
| EFFICACY (LM/W) | 133 |
| CIRCUIT WATTAGE (W) | 22.6 |
| ССТ | 3000/4000/6000K |
| CRI | >85 |
| SDCM | <6 |
| RUNNING CURRENT (A) | 0.09 |
| DISPLACEMENT FACTOR | >0.7 |
| SVM | 0.005 |
| PST-LM | 0.12 |
| BEAM ANGLE (DEGREES) | 110 |
| LIFE SPAN (HRS) | 50,000 |
| L70B50 LIFESPAN (HRS) | 50,000 |
| LED COMPATIBLE | Yes |





Xnightsbridge

| DIMMABLE | No |
|--|---|
| OPERATING TEMPERATURE | -20~50°C |
| INPUT VOLTAGE | 230V 50Hz |
| CABLE ENTRY (MM) | 20 |
| CABLE GLAND INCLUDED | Blind grommet |
| DRIVER | DRIVER TYPE - Constant Current MAX. OUTPUT - 21W OUTPUT VOLTAGE - 28-42V OUTPUT CURRENT - 500mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 86 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - 50°C CASE TEMPERATURE (Tc) - 90°C |
| SENSOR TYPE | Photocell |
| SENSOR LUX SETTINGS | 5-25lx - 200-400lx |
| WARRANTY | 5year(s) |
| MANUFACTURED IN ACCORDANCE WITH | BS EN 60598 |
| ORIGIN OF MANUFACTURE | China |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes |
| EAN | 5056270800272 |

Date Created: 27/02/2025 12:50





