Xnightsbridge

DATASHEET



CL63NBC

13A Switched Fused Spur Unit with Neon - Brushed Chrome

www.mlaccessories.co.uk

DESCRIPTION NET WEIGHT (KG) FINISH Brushed Chrome Height - 85.75 Width - 85.75 Depth - 27.29 Projection - 12.6 MINIMUM MOUNTING BOX DEPTH CONSTRUCTION CLASS I IP RATING IP20 INPUT VOLTAGE SWITCH TYPE Double Pole	
FINISH Brushed Chrome Height - 85.75 Width - 85.75 Depth - 27.29 Projection - 12.6 MINIMUM MOUNTING BOX DEPTH CONSTRUCTION CONSTRUCTION CONSTRUCTION IP RATING IP20 INPUT VOLTAGE SWITCH TYPE Brushed Chrome Height - 85.75 Width - 85.75 Depth - 27.29 Projection - 12.6 Construction - 304 Stainless steel I IP20 Double Pole	ome
DIMENSIONS (MM) Height - 85.75 Width - 85.75 Depth - 27.29 Projection - 12.6 MINIMUM MOUNTING BOX DEPTH CONSTRUCTION Construction - 304 Stainless steel CLASS I IP20 INPUT VOLTAGE SWITCH TYPE Double Pole	
DIMENSIONS (MM) Width - 85.75 Depth - 27.29 Projection - 12.6 MINIMUM MOUNTING BOX DEPTH CONSTRUCTION Construction - 304 Stainless steel CLASS I IP RATING IP20 INPUT VOLTAGE SWITCH TYPE Double Pole	
CONSTRUCTION CLASS I IP RATING INPUT VOLTAGE SWITCH TYPE Construction - 304 Stainless steel I Construction - 304 Stainless steel I Double Pole	
CLASS I PRATING IP20 INPUT VOLTAGE 230V 50Hz SWITCH TYPE Double Pole	
IP RATING IP20 INPUT VOLTAGE 230V 50Hz SWITCH TYPE Double Pole	
INPUT VOLTAGE 230V 50Hz SWITCH TYPE Double Pole	
SWITCH TYPE Double Pole	
CARTILITEDMINAL Yes	
EARTH TERMINAL Yes	
NEON INDICATOR Yes	
LOAD/MAX. LOAD 13A	
TERMINAL CAPACITY 3 x 2.5mm² or 2 x 4.0mm²	
WARRANTY 25year(s)	
MANUFACTURED IN ACCORDANCE WITH BS 1363-4	
ORIGIN OF MANUFACTURE China	
DECLARATION OF CONFORMITY (HELD ON FILE) Yes	
EAN 5055832910305	

Date Created: 27/02/2025 09:07





