


DATASHEET



BT9ACTB

230V IP65 9W CCT Adjustable LED Bulkhead C/W Black Trim

www.mlaccessories.co.uk



| MLA PART CODE | BT9ACTB |
|-------------------------------|---|
| DESCRIPTION | 230V IP65 9W CCT Adjustable LED Bulkhead C/W Black Trim |
| NET WEIGHT (KG) | 0.6 |
| FINISH | Black |
| DIFFUSER | Opal |
| DIMENSIONS (MM) | Diameter - 256 Projection - 74 |
| CONSTRUCTION | Construction - Polycarbonate |
| CLASS | II |
| IP RATING | IP65 |
| IK RATING | IK08 |
| WATTAGE (W) | 9 |
| LAMP TECHNOLOGY | SMD LED |
| LAMP INCLUDED | Yes |
| LUMENS (LM) | 730 / 810 / 780 |
| LUMENS LIGHT SOURCE ONLY (LM) | 900 |
| LUMEN TOLERANCE | 5% |
| EFFICACY (LM/W) | 119 |
| CIRCUIT WATTAGE (W) | 7.617 |
| CCT | 3000/4000/5700K |
| LIGHT COLOUR | CCT |
| CRI | >80 |
| SDCM | <6 |
| RUNNING CURRENT (A) | 0.036 |
| DISPLACEMENT FACTOR | >0.9 |
| SVM | 0.536 |
| PST-LM | 0.025 |
| BEAM ANGLE (DEGREES) | 115 |
| LIFE SPAN (HRS) | 30,000 |

| | |
|--|--|
| L70B50 LIFESPAN (HRS) | 50,000 |
| LED COMPATIBLE | Yes |
| DIMMABLE | No |
| OPERATING TEMPERATURE | -20~50°C |
| INPUT VOLTAGE | 230V 50Hz |
| CABLE ENTRY (MM) | 20 |
| CABLE GLAND INCLUDED | Blind grommet |
| DRIVER | DRIVER TYPE - Constant Current MAX. OUTPUT - 8.6W OUTPUT VOLTAGE - 30 - 43V OUTPUT CURRENT - 200mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 80 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - -20~50°C CASE TEMPERATURE (Tc) - 75°C |
| WARRANTY | 5year(s) |
| MANUFACTURED IN ACCORDANCE WITH | BS EN 60598 |
| ORIGIN OF MANUFACTURE | China |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes |
| EAN | 5056270827972 |

Date Created: 27/02/2025 17:31

