


DATASHEET



BATSCW4

230V 4ft 18/32W CCT Adjustable Batten

www.mlaccessories.co.uk



| MLA PART CODE | BATSCW4 |
|-------------------------------|--|
| DESCRIPTION | 230V 4ft 18/32W CCT Adjustable Batten |
| NET WEIGHT (KG) | 1.34 |
| FINISH | White |
| DIFFUSER | Opal |
| DIMENSIONS (MM) | Length - 1225 Width - 61 Projection - 71 |
| CONSTRUCTION | Construction - Pressed steel Construction 2 - & polycarbonate |
| CLASS | I |
| IP RATING | IP20 |
| WATTAGE (W) | 18/32 |
| LAMP TECHNOLOGY | LED |
| LUMENS (LM) | 2380/2600/2570, 3950/4490/4310 |
| LUMENS LIGHT SOURCE ONLY (LM) | 5020 |
| LUMEN TOLERANCE | 5% |
| EFFICACY (LM/W) | 159.14 |
| CIRCUIT WATTAGE (W) | 31.6 |
| CCT | 3000/4000/5700K |
| LIGHT COLOUR | CCT |
| CRI | >85 |
| SDCM | <6 |
| RUNNING CURRENT (A) | 0.142 |
| DISPLACEMENT FACTOR | >0.9 |
| SVM | 0 |
| PST-LM | 0 |
| BEAM ANGLE (DEGREES) | 145 |
| L70B50 LIFESPAN (HRS) | 60,000 |
| DIMMABLE | No |

| | |
|---|--|
| OPERATING TEMPERATURE | -20~50°C |
| INPUT VOLTAGE | 230V 50Hz |
| CABLE GLAND INCLUDED | No |
| DRIVER | DRIVER TYPE - Constant Current MAX. OUTPUT - 16/31W OUTPUT VOLTAGE - 30-43V OUTPUT CURRENT - 360/720mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 97.4 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - -20~50°C CASE TEMPERATURE (Tc) - 75°C |
| WARRANTY | 5year(s) |
| ORIGIN OF MANUFACTURE | China |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes |
| EAN | 5056270881332 |

Date Created: 27/02/2025 19:32

