## **X**nightsbridge

## **DATASHEET**



## **EMRNSTL**230V 4W LED Emergency Exit Sign - Self-test

www.mlaccessories.co.uk

MLA PART CODE	EMRNSTL
DESCRIPTION	230V 4W LED Emergency Exit Sign - Self-test
NET WEIGHT (KG)	0.57
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 324 Height - 169 Projection - 42
CONSTRUCTION	Construction - Polycarbonate
CLASS	II
IP RATING	IP20
WATTAGE (W)	4
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	150
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	37
LUMENS EMERGENCY MODE (LM)	120
CIRCUIT WATTAGE (W)	4.08
ССТ	6000K
LIGHT COLOUR	Daylight
CRI	>80
RUNNING CURRENT (A)	0.033
SVM	0.04
BEAM ANGLE (DEGREES)	110
LIFE SPAN (HRS)	30,000
DIMMABLE	No
EMERGENCY	Maintained / Non-maintained / Switched
SELF-TEST	Yes
OPERATING TEMPERATURE	0~45°C





## **X**nightsbridge

INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	2 x 20
CABLE GLAND INCLUDED	No
BATTERY TYPE	LiFePO4
BATTERY INCLUDED	Yes
WARRANTY	3year(s)
WARRANTY INFORMATION	including battery
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270834987

Date Created: 28/02/2025 00:34





