Xnightsbridge

DATASHEET



FP1100PC

10A Fan Isolator Switch - Polished Chrome

www.mlaccessories.co.uk

DESCRIPTION NET WEIGHT (KG) FINISH Polished Chrome Height - 87.5 Width - 87.5 Depth - 21.6 Projection - 6.8 Recessed Depth - 14.8 MINIMUM MOUNTING BOX DEPTH CONSTRUCTION IP20 INPUT VOLTAGE SWITCH FUNCTION EARTH TERMINAL LOAD/MAX. LOAD TERMINAL CAPACITY ADDITIONAL FEATURES WARRANTY MANUFACTURED 10A Fan Isolator Switch - Polished Chrome 10.09 10A Fan Isolator Switch - Polished Chrome 10B O.09 10B O.	MLA PART CODE	FP1100PC
FINISH Polished Chrome Height - 87.5 Width - 87.5 Depth - 21.6 Projection - 6.8 Recessed Depth - 14.8 MINIMUM MOUNTING BOX DEPTH CONSTRUCTION CONSTRUCTION IP RATING IP20 INPUT VOLTAGE SWITCH FUNCTION Fan Isolator EARTH TERMINAL Yes LOAD/MAX. LOAD TERMINAL CAPACITY ADDITIONAL FEATURES WARRANTY WARRANTY BS EN 60669-1, BS EN 60669-2-4 ORIGIN OF MANUFACTURE Height - 87.5 Width -	DESCRIPTION	10A Fan Isolator Switch - Polished Chrome
DIMENSIONS (MM) Height - 87.5 Width - 87.5 Depth - 21.6 Projection - 6.8 Recessed Depth - 14.8 MINIMUM MOUNTING BOX DEPTH CONSTRUCTION CONSTRUCTION IP20 INPUT VOLTAGE SWITCH FUNCTION EARTH TERMINAL LOAD/MAX. LOAD TERMINAL CAPACITY ADDITIONAL FEATURES WARRANTY MANUFACTURED IN ACCORDANCE WITH DIMENSIONS (MM) Height - 87.5 Width - 87.5 Depth - 21.6 Projection - 6.8 Recessed Depth - 14.8 Construction - 201 Stainless steel IP20 INPUT VOLTAGE 230V 50Hz Fan Isolator Fan Isolator 2 x 1.0mm² or 2 x 1.5mm² ADDITIONAL FEATURES Triple Pole WARRANTY BS EN 60669-1, BS EN 60669-2-4 ORIGIN OF MANUFACTURE China	NET WEIGHT (KG)	0.09
DIMENSIONS (MM) DIMENSIONS (MM) DIMENSIONS (MM) Width - 87.5 Depth - 21.6 Projection - 6.8 Recessed Depth - 14.8 MINIMUM MOUNTING BOX DEPTH Tonstruction - 201 Stainless steel IP RATING IP20 INPUT VOLTAGE SWITCH FUNCTION Fan Isolator EARTH TERMINAL LOAD/MAX. LOAD TERMINAL CAPACITY ADDITIONAL FEATURES Triple Pole WARRANTY MANUFACTURED IN ACCORDANCE WITH DIAM Width - 87.5 Depth - 21.6 Projection - 6.8 Recessed Depth - 14.8 Inem 104. EARTH 105. Width - 87.5 Depth - 21.6 Projection - 6.8 Recessed Depth - 14.8 Inem 201 Stainless steel IP20 IP20 INPUT VOLTAGE 230V 50Hz SWITCH FUNCTION Fan Isolator EARTH TERMINAL Yes LOAD/MAX. LOAD Tona Triple Pole WARRANTY BS EN 60669-1, BS EN 60669-2-4 ORIGIN OF MANUFACTURE	FINISH	Polished Chrome
CONSTRUCTION Construction - 201 Stainless steel IP RATING IP20 INPUT VOLTAGE SWITCH FUNCTION EARTH TERMINAL LOAD/MAX. LOAD TERMINAL CAPACITY ADDITIONAL FEATURES WARRANTY MANUFACTURED IN ACCORDANCE WITH ORIGIN OF MANUFACTURE China IP20 230V 50Hz Fan Isolator Fan Isolator Yes 10A 2 x 1.0mm² or 2 x 1.5mm² Triple Pole 8 EN 60669-1, BS EN 60669-2-4 China	DIMENSIONS (MM)	Width - 87.5 Depth - 21.6 Projection - 6.8
IP RATING INPUT VOLTAGE 230V 50Hz SWITCH FUNCTION Fan Isolator EARTH TERMINAL Yes LOAD/MAX. LOAD 10A TERMINAL CAPACITY 2 x 1.0mm² or 2 x 1.5mm² ADDITIONAL FEATURES Triple Pole WARRANTY 25year(s) MANUFACTURED IN ACCORDANCE WITH BS EN 60669-1, BS EN 60669-2-4 ORIGIN OF MANUFACTURE China	MINIMUM MOUNTING BOX DEPTH	16mm
INPUT VOLTAGE SWITCH FUNCTION Fan Isolator Yes LOAD/MAX. LOAD TERMINAL CAPACITY ADDITIONAL FEATURES WARRANTY MANUFACTURED IN ACCORDANCE WITH TIPLE POLE SEN 60669-1, BS EN 60669-2-4 China	CONSTRUCTION	Construction - 201 Stainless steel
SWITCH FUNCTION EARTH TERMINAL Yes LOAD/MAX. LOAD TERMINAL CAPACITY ADDITIONAL FEATURES Triple Pole WARRANTY MANUFACTURED IN ACCORDANCE WITH ORIGIN OF MANUFACTURE Fan Isolator Yes 10A 2 x 1.0mm² or 2 x 1.5mm² 2 x 1.0mm² or 2 x 1.5mm² BY SEN 60669-1, BS EN 60669-2-4 China	IP RATING	IP20
EARTH TERMINAL LOAD/MAX. LOAD TERMINAL CAPACITY ADDITIONAL FEATURES WARRANTY MANUFACTURED IN ACCORDANCE WITH ORIGIN OF MANUFACTURE Yes 10A 2 x 1.0mm² or 2 x 1.5mm² Triple Pole 25year(s) BS EN 60669-1, BS EN 60669-2-4 China	INPUT VOLTAGE	230V 50Hz
LOAD/MAX. LOAD TERMINAL CAPACITY ADDITIONAL FEATURES Triple Pole WARRANTY 25year(s) MANUFACTURED IN ACCORDANCE WITH ORIGIN OF MANUFACTURE China	SWITCH FUNCTION	Fan Isolator
TERMINAL CAPACITY 2 x 1.0mm² or 2 x 1.5mm² ADDITIONAL FEATURES Triple Pole WARRANTY 25year(s) MANUFACTURED IN ACCORDANCE WITH BS EN 60669-1, BS EN 60669-2-4 ORIGIN OF MANUFACTURE China	EARTH TERMINAL	Yes
ADDITIONAL FEATURES Triple Pole WARRANTY 25year(s) MANUFACTURED IN ACCORDANCE WITH BS EN 60669-1, BS EN 60669-2-4 ORIGIN OF MANUFACTURE China	LOAD/MAX. LOAD	10A
WARRANTY 25year(s) MANUFACTURED IN ACCORDANCE WITH BS EN 60669-2-4 ORIGIN OF MANUFACTURE China	TERMINAL CAPACITY	2 x 1.0mm² or 2 x 1.5mm²
MANUFACTURED IN ACCORDANCE WITH BS EN 60669-1, BS EN 60669-2-4 China	ADDITIONAL FEATURES	Triple Pole
ORIGIN OF MANUFACTURE China	WARRANTY	25year(s)
	MANUFACTURED IN ACCORDANCE WITH	BS EN 60669-1, BS EN 60669-2-4
DECLARATION OF CONFORMITY (HELD ON FILE)	ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN 5055832916871	EAN	5055832916871

Date Created: 28/02/2025 22:13





