## Knightsbridge


230V 6W LED Shaver Light with Dual Voltage Socket

## DATASHEET



## SLIGHT2

www.mlaccessories.co.uk



A PART CODESLIGHT2SCRIPTION230V 6W LED Shaver Light with Dual Voltage SocketT WEIGHT (KG)0.929IISHWhiteFUSERPrismaticMENSIONS (MM)Height - 59 Width - 494 Projection - 70INSTRUCTIONConstruction - PolycarbonateASSIIRATINGIP20XTAGE (W)6X. WATTAGE (W)6MP EASES15MP INCLUDEDYesMENS (LM)450MENS LIGHT SOURCE ONLY (LM)640MEN TOLERANCE5%FICACY (LM/W)105	
T WEIGHT (KG)0.929IISH0.929IISHWhiteFFUSERPrismaticMENSIONS (MM)Height - 59 Width - 494 Projection - 70NSTRUCTIONConstruction - PolycarbonateASSIIRATINGIP20TTAGE (W)6X. WATTAGE (W)6MP TECHNOLOGYLEDMP BASES15MP INCLUDEDYesMENS (LM)640MENS LIGHT SOURCE ONLY (LM)5%	
IISHWhiteFFUSERPrismaticIENSIONS (MM)Height - 59 Width - 494 Projection - 70INSTRUCTIONConstruction - PolycarbonateASSIIRATINGIP20ITTAGE (W)6XX. WATTAGE (W)6MP TECHNOLOGYLEDMP BASES15MP INCLUDEDYesMENS (LM)450MENS LIGHT SOURCE ONLY (LM)5%	
Height - 59 Width - 494 Projection - 70NSTRUCTIONConstruction - PolycarbonateASSIIRATINGIP20TTAGE (W)6MP TECHNOLOGYLEDMP BASES15MP INCLUDEDYesMENS (LM)640MENS LIGHT SOURCE ONLY (LM)640	
MENSIONS (MM)Width - 494 Projection - 70NSTRUCTIONConstruction - PolycarbonateASSIIRATINGIP20ITTAGE (W)6X. WATTAGE (W)6MP TECHNOLOGYLEDMP BASES15MP INCLUDEDYesMENS (LM)640MENS LIGHT SOURCE ONLY (LM)640	
ASS II II RATING IIP20 ITTAGE (W) 6 X. WATTAGE (W) 6 MP TECHNOLOGY ILED MP BASE S15 MP INCLUDED Yes MENS (LM) 450 MENS LIGHT SOURCE ONLY (LM) 640 MEN TOLERANCE 5%	
RATINGIP20TTAGE (W)6X. WATTAGE (W)6MP TECHNOLOGYLEDMP BASES15MP INCLUDEDYesMENS (LM)450MENS LIGHT SOURCE ONLY (LM)640MEN TOLERANCE5%	
ATTAGE (W)6X. WATTAGE (W)6MP TECHNOLOGYLEDMP BASES15MP INCLUDEDYesMENS (LM)450MENS LIGHT SOURCE ONLY (LM)640MEN TOLERANCE5%	
X. WATTAGE (W)6MP TECHNOLOGYLEDMP BASES15MP INCLUDEDYesMENS (LM)450MENS LIGHT SOURCE ONLY (LM)640MEN TOLERANCE5%	
MP TECHNOLOGYLEDMP BASES15MP INCLUDEDYesMENS (LM)450MENS LIGHT SOURCE ONLY (LM)640MEN TOLERANCE5%	
MP BASES15MP INCLUDEDYesMENS (LM)450MENS LIGHT SOURCE ONLY (LM)640MEN TOLERANCE5%	
MP INCLUDEDYesMENS (LM)450MENS LIGHT SOURCE ONLY (LM)640MEN TOLERANCE5%	
MENS (LM)450MENS LIGHT SOURCE ONLY (LM)640MEN TOLERANCE5%	
MENS LIGHT SOURCE ONLY (LM)640MEN TOLERANCE5%	
MEN TOLERANCE 5%	
FICACY (LM/W) 105	
RCUIT WATTAGE (W) 6.2	
т 3000К	
COLOUR Warm White	
I >80	
CM <6	
NNING CURRENT (A) 0.026	
SPLACEMENT FACTOR >0.7	
M 0.01	
T-LM 0.03	
E SPAN (HRS) 30,000	





## Knightsbridge

L70B50 LIFESPAN (HRS)	25,000
LED COMPATIBLE	Yes
DIMMABLE	No
OPERATING TEMPERATURE	25°C
INPUT VOLTAGE	230V 50Hz
SECONDARY VOLTAGE	115/230V
LOAD/MAX. LOAD	20
WARRANTY	1year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598, EN 61558-2-5
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832987659
Data Croated: 27/02/2025 12:16	

Date Created: 27/02/2025 12:16





