Xnightsbridge


DATASHEET



AMLEDBP

230V IP54 5W LED Security Amenity Bulkhead with Daylight Sensor - Black

www.mlaccessories.co.uk



| MLA PART CODE | AMLEDBP |
|-------------------------------|---|
| DESCRIPTION | 230V IP54 5W LED Security Amenity Bulkhead with Daylight Sensor - Black |
| NET WEIGHT (KG) | 0.272 |
| FINISH | Black |
| DIFFUSER | Opal |
| DIMENSIONS (MM) | Length - 78 Height - 197 Width - 108 Projection - 78 |
| CONSTRUCTION | Construction - Polycarbonate |
| CLASS | II |
| IP RATING | IP54 |
| IK RATING | IK03 |
| WATTAGE (W) | 5 |
| LAMP TECHNOLOGY | SMD LED |
| LAMP INCLUDED | Yes |
| LUMENS (LM) | 460 |
| LUMENS LIGHT SOURCE ONLY (LM) | 520 |
| LUMEN TOLERANCE | 5% |
| EFFICACY (LM/W) | 100 |
| CIRCUIT WATTAGE (W) | 5.3 |
| ССТ | 4000K |
| LIGHT COLOUR | Cool White |
| CRI | >80 |
| SDCM | <6 |
| RUNNING CURRENT (A) | 0.023 |
| DISPLACEMENT FACTOR | >0.9 |
| SVM | 0.001 |
| PST-LM | 0.185 |
| BEAM ANGLE (DEGREES) | 120 |





Xnightsbridge

| LIFE SPAN (HRS) | 30,000 |
|--|--|
| L70B50 LIFESPAN (HRS) | 60,000 |
| DIMMABLE | No |
| OPERATING TEMPERATURE | -20~50°C |
| INPUT VOLTAGE | 230V 50Hz |
| CABLE ENTRY (MM) | 20 |
| DRIVER | MAX. OUTPUT - 5W OUTPUT VOLTAGE - 29-35V OUTPUT CURRENT - 150mA POWER FACTOR - 0.46 EFFICIENCY FULL LOAD - 85 CASE TEMPERATURE (Tc) - 80°C |
| SENSOR TYPE | Photocell |
| SENSOR OVERRIDE | No |
| SENSOR LUX SETTINGS | 10-80lx/Disable |
| STANDBY POWER | 0.1W |
| WARRANTY | 3year(s) |
| MANUFACTURED IN ACCORDANCE WITH | BS EN 60598 |
| ORIGIN OF MANUFACTURE | China |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes |
| EAN | 5056270822885 |
| D-1- O | |

Date Created: 27/02/2025 16:32





