Xnightsbridge


DATASHEET



BT20ACTDALI

230V IP65 20W CCT Adjustable DALI LED Bulkhead

www.mlaccessories.co.uk





MLA PART CODE	BT20ACTDALI
DESCRIPTION	230V IP65 20W CCT Adjustable DALI LED Bulkhead
NET WEIGHT (KG)	1.2
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Diameter - 380 Projection - 81
CONSTRUCTION	Construction - Polycarbonate
CLASS	II
IP RATING	IP65
IK RATING	IK08
WATTAGE (W)	20
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	1820/2070/2010
LUMENS LIGHT SOURCE ONLY (LM)	2580/2740/2665
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	138
CIRCUIT WATTAGE (W)	19.9
ССТ	3000/4000/5700K
LIGHT COLOUR	ССТ
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.090
DISPLACEMENT FACTOR	>0.9
SVM	0.017
PST-LM	0.027
BEAM ANGLE (DEGREES)	115
L70B50 LIFESPAN (HRS)	50,000





Xnightsbridge

LED COMPATIBLE	Yes
OPERATING TEMPERATURE	-20~45°C
INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	Blind grommet
WARRANTY	5year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270844429
Data Organia di 00/00/000E 01:01	

Date Created: 28/02/2025 01:01





