



DATASHEET



BATSCWMEM4

230V 4ft 18/32W CCT Adjustable with Emergency and Microwave Batten

www.mlaccessories.co.uk



MLA PART CODE	BATSCWMEM4
DESCRIPTION	230V 4ft 18/32W CCT Adjustable with Emergency and Microwave Batten
NET WEIGHT (KG)	1.6
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1225 Width - 61 Projection - 71
CONSTRUCTION	Construction - Pressed steel Construction 2 - & polycarbonate
CLASS	I
IP RATING	IP20
WATTAGE (W)	18/32
LAMP TECHNOLOGY	LED
LUMENS (LM)	2380/2600/2570, 3950/4490/4310
LUMENS LIGHT SOURCE ONLY (LM)	5020
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	159.14
LUMENS EMERGENCY MODE (LM)	320
CIRCUIT WATTAGE (W)	31.6
CCT	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.142
DISPLACEMENT FACTOR	>0.9
SVM	0
PST-LM	0
BEAM ANGLE (DEGREES)	145
L70B50 LIFESPAN (HRS)	60,000

DIMMABLE	No
EMERGENCY	Maintained / Non-maintained / Switched
SELF-TEST	No
OPERATING TEMPERATURE	-5~50°C
INPUT VOLTAGE	230V 50Hz
CABLE GLAND INCLUDED	No
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 16/31W OUTPUT VOLTAGE - 30-43V OUTPUT CURRENT - 360/720mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 97.1 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - -20~50°C CASE TEMPERATURE (Tc) - 75°C
SENSOR TYPE	Microwave
SENSOR OVERRIDE	No
SENSOR DETECTION ANGLE (DEGREES)	150 (wall mounted) / 360 (ceiling mounted)
OPTIMUM DETECTION RANGE (M)	6m at height 3m, max. mounting height 6m
SENSOR DURATION	5 seconds - 30 minutes
BATTERY TYPE	LiFePO4
SENSOR LUX SETTINGS	2 lux - 50 lux / Disable
BATTERY INCLUDED	Yes
STANDBY POWER	≤ 0.5WW
WARRANTY	5year(s)
WARRANTY INFORMATION	(excluding battery)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270881677

Date Created: 27/02/2025 19:55

