Xnightsbridge

DATASHEET



EMPOWER4

230V IP20 3.5W LED Emergency Downlight 5500K (maintained/non-maintained use)

www.mlaccessories.co.uk

MLA PART CODE	EMPOWER4
DESCRIPTION	230V IP20 3.5W LED Emergency Downlight 5500K (maintained/non-maintained use)
NET WEIGHT (KG)	0.22
FINISH	White
DIMENSIONS (MM)	Diameter - 60 Length - 184 Height - 31 Width - 31 Recessed Depth - 32 Minimum Void - 80
CUT-OUT (MM)	Cut-out Diameter - 45
CONSTRUCTION	Construction - Polycarbonate
CLASS	II
IP RATING	IP20
WATTAGE (W)	3.5
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	140
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	40
LUMENS EMERGENCY MODE (LM)	140
CIRCUIT WATTAGE (W)	3.5
ССТ	5500K
LIGHT COLOUR	Daylight
CRI	>70
RUNNING CURRENT (A)	0.027
BEAM ANGLE (DEGREES)	140
L70B50 LIFESPAN (HRS)	30000
DIMMABLE	No
EMERGENCY	Maintained / Non-maintained / Switched





Xnightsbridge

SELF-TEST	No
IC RATED	No
OPERATING TEMPERATURE	0~25°C
INPUT VOLTAGE	230V 50Hz
CABLE LENGTH (M)	0.35
CABLE TYPE	H05VV-F
BATTERY TYPE	LiFePO4
BATTERY INCLUDED	Yes
WARRANTY	5year(s)
WARRANTY INFORMATION	including battery
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270877595

Date Created: 27/02/2025 18:36





