Xnightsbridge

DATASHEET



SFR9945BC

13A 2G DP Switched Socket with Dual USB A+C 20V DC 2.25A (Max. 45W) - Brushed Chrome w/Black Insert

www.mlaccessories.co.uk

MLA PART CODE	SFR9945BC
DESCRIPTION	13A 2G DP Switched Socket with Dual USB A+C 20V DC 2.25A (Max. 45W) - Brushed Chrome w/Black Insert
NET WEIGHT (KG)	0.284
FINISH	Brushed Chrome
INSERT COLOUR	Black
DIMENSIONS (MM)	Height - 87.5 Width - 147.5 Depth - 33.77 Projection - 9.3 Recessed Depth - 24.47
MINIMUM MOUNTING BOX DEPTH	25-35mm (dependent on wiring conditions)
CONSTRUCTION	Construction - 201 Stainless steel
CLASS	I
IP RATING	IP20
INPUT VOLTAGE	230V 50Hz
SWITCH TYPE	Double Pole
EARTH TERMINAL	Yes
LOAD/MAX. LOAD	13A
TERMINAL TYPE	Captive
TERMINAL CAPACITY	2 x 2.5mm² or 1 x 4.0mm²
NO. OF USB PORTS	2
NO. OF TYPE-A PORTS	1
NO. OF TYPE-C PORTS	1
USB CHARGING	20V DC 2.25A
ADDITIONAL FEATURES	USB-C ONLY: 5V DC 3A (15W) / 9V DC 3A (27W) / 15V DC 3A (45W) / 20V DC 2.25A (45W) USB-A ONLY: 5V DC 3A (15W) / 9V DC 2A (18W) / 12V DC 1.5A (18W) BOTH PORTS IN USE: USB-C: 5V DC 3A (15W) / 9V DC 3A (27W) / 20V DC 1.35A (27W), USB-A: 5V DC 3A (15W) / 9V DC 2A (18W) / 12V DC 1.5A (18W)
WARRANTY	2year(s)
MANUFACTURED IN ACCORDANCE WITH	BS 1363-2, EN 62368-1







ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270848250

Date Created: 28/02/2025 01:05





