


## DATASHEET



### SER3040DALI

SEREN 230V IP40 LED Recessed Tri-Wattage and CCT DALI Downlight - 30/ 35/ 40W

[www.mlaccessories.co.uk](http://www.mlaccessories.co.uk)



MLA PART CODE	SER3040DALI
DESCRIPTION	SEREN 230V IP40 LED Recessed Tri-Wattage and CCT DALI Downlight - 30/ 35/ 40W
NET WEIGHT (KG)	1.02
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Diameter - 220 Recessed Depth - 69.5 Minimum Void - 100
CUT-OUT (MM)	Cut-out Diameter - 200
CONSTRUCTION	Construction - Aluminium Construction 2 - & polycarbonate
CLASS	II
IP RATING	IP40 (IP20 from above)
WATTAGE (W)	30 / 35 / 40
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	3665/3460/3600/4275/4230/4130/4710/4745/4900
LUMENS LIGHT SOURCE ONLY (LM)	6510
LUMEN TOLERANCE	10%
EFFICACY (LM/W)	180
CIRCUIT WATTAGE (W)	36.23
CCT	3000/4000/5000K
LIGHT COLOUR	CCT
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.166
DISPLACEMENT FACTOR	>0.7
SVM	0.01
PST-LM	0.575
BEAM ANGLE (DEGREES)	110

L70B50 LIFESPAN (HRS)	50,000
LED COMPATIBLE	Yes
EMERGENCY CONVERSION KIT	EMKIT2L
IC RATED	No
OPERATING TEMPERATURE	-25~45°C
INPUT VOLTAGE	230V 50Hz
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 45W OUTPUT VOLTAGE - 25-70V OUTPUT CURRENT - 350/500/600/700/800/900/1050mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 87 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - -20~50°C CASE TEMPERATURE (Tc) - 85°C
WARRANTY	5year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270846379

Date Created: 28/02/2025 01:03

