Xnightsbridge

DATASHEET



SFR9124PCG

13A 1G SP Switched Socket with Dual USB A+A (5V DC 2.4A shared) - Polished Chrome with Grey Insert

www.mlaccessories.co.uk

NET WEIGHT (KG) 0.18	MLA PART CODE	SFR9124PCG
FINISH Polished Chrome Grey Height - 87.5 Width - 87.5 Width - 87.5 Depth - 34.3 Projection - 9.6 Recessed Depth - 24.7 MINIMUM MOUNTING BOX DEPTH 25-35mm (dependent on wiring conditions) CONSTRUCTION IP20 INPUT VOLTAGE Single Pole EARTH TERMINAL Yes Single Pole EARTH TERMINAL Yes LOAD/MAX. LOAD 13A TERMINAL CAPACITY 2 x 2.5mm² or 1 x 4.0mm² NO. OF USB PORTS 2 USB CHARGING 5V DC 2.4A (shared) ADDITIONAL FEATURES Overload and short circuit protection STANDBY POWER 0.1W WARRANTY 2year(s) MANUISACTURED IN ACCORDANCE WITH PS 1363-2 BS EN 62368-1	DESCRIPTION	13A 1G SP Switched Socket with Dual USB A+A (5V DC 2.4A shared) - Polished Chrome with Grey Insert
DIMENSIONS (MM) Height - 87.5 Width - 87.5 Depth - 34.3 Projection - 9.6 Recessed Depth - 24.7	NET WEIGHT (KG)	0.18
DIMENSIONS (MM) Height - 87.5 Width - 87.5 Depth - 34.3 Projection - 9.6 Recessed Depth - 24.7 MINIMUM MOUNTING BOX DEPTH 25-35mm (dependent on wiring conditions) CONSTRUCTION CONSTRUCTION CONSTRUCTION CONSTRUCTION IP20 INPUT VOLTAGE Single Pole EARTH TERMINAL Yes LOAD/MAX. LOAD 13A TERMINAL CAPACITY 2 x 2.5mm² or 1 x 4.0mm² NO. OF USB PORTS 2 USB CHARGING ADDITIONAL FEATURES Overload and short circuit protection STANDBY POWER WARRANTY PS 1563-2 RS EN 62368-1	FINISH	Polished Chrome
DIMENSIONS (MM) Width - 87.5 Depth - 34.3 Projection - 9.6 Recessed Depth - 24.7 MINIMUM MOUNTING BOX DEPTH 25-35mm (dependent on wiring conditions) CONSTRUCTION Construction - 201 Stainless steel IP20 INPUT VOLTAGE SINGLE POLE EARTH TERMINAL Yes LOAD/MAX. LOAD 13A TERMINAL CAPACITY NO. OF USB PORTS 2 V 2.55mm² or 1 x 4.0mm² NO. OF TYPE-A PORTS 2 USB CHARGING ADDITIONAL FEATURES Overload and short circuit protection STANDBY POWER WARRANTY PS 1363-2 RS EN 62368-1	INSERT COLOUR	Grey
CONSTRUCTION Construction - 201 Stainless steel I IP RATING IP20 INPUT VOLTAGE SWITCH TYPE Single Pole EARTH TERMINAL Yes LOAD/MAX. LOAD 13A TERMINAL CAPACITY 2 x 2.5mm² or 1 x 4.0mm² NO. OF USB PORTS 2 NO. OF TYPE-A PORTS 2 USB CHARGING ADDITIONAL FEATURES Overload and short circuit protection STANDBY POWER 0.1W WARRANTY PS 1363-2 PS EN 62368-1	DIMENSIONS (MM)	Width - 87.5 Depth - 34.3 Projection - 9.6 Recessed Depth - 24.7
I	MINIMUM MOUNTING BOX DEPTH	, ,
IP RATING IPPO INPUT VOLTAGE SWITCH TYPE Single Pole EARTH TERMINAL LOAD/MAX. LOAD TERMINAL CAPACITY NO. OF USB PORTS NO. OF TYPE-A PORTS USB CHARGING ADDITIONAL FEATURES STANDBY POWER WARRANTY PS 1363-2 PS EN 62368-1	CONSTRUCTION	Construction - 201 Stainless steel
Single Pole	CLASS	I
SWITCH TYPE EARTH TERMINAL Yes LOAD/MAX. LOAD 13A TERMINAL CAPACITY 2 x 2.5mm² or 1 x 4.0mm² NO. OF USB PORTS 2 NO. OF TYPE-A PORTS 2 USB CHARGING ADDITIONAL FEATURES Overload and short circuit protection STANDBY POWER WARRANTY Single Pole Yes 13A 2 x 2.5mm² or 1 x 4.0mm² 2 x 2.5mm² or 1 x 4.0mm² 2 v 3 v 3 v 4.0mm² 2 v 4 v 4.0mm² 2 v 4 v 4 v 4 v 4 v 4 v 4 v 4 v 4 v 4 v	IP RATING	IP20
EARTH TERMINAL LOAD/MAX. LOAD 13A TERMINAL CAPACITY 2 x 2.5mm² or 1 x 4.0mm² NO. OF USB PORTS 2 NO. OF TYPE-A PORTS 2 USB CHARGING ADDITIONAL FEATURES Overload and short circuit protection STANDBY POWER WARRANTY 2year(s) MANUFACTURED IN ACCORDANCE WITH PS 1363-2 RS EN 62368-1	INPUT VOLTAGE	230V 50Hz
LOAD/MAX. LOAD TERMINAL CAPACITY 2 x 2.5mm² or 1 x 4.0mm² NO. OF USB PORTS 2 NO. OF TYPE-A PORTS 2 USB CHARGING 5V DC 2.4A (shared) ADDITIONAL FEATURES Overload and short circuit protection STANDBY POWER 0.1W WARRANTY 2year(s) MANUFACTURED IN ACCORDANCE WITH BS 1363-2 BS EN 62368-1	SWITCH TYPE	Single Pole
TERMINAL CAPACITY 2 x 2.5mm² or 1 x 4.0mm² NO. OF USB PORTS 2 NO. OF TYPE-A PORTS 2 USB CHARGING ADDITIONAL FEATURES Overload and short circuit protection STANDBY POWER O.1W WARRANTY 2year(s) MANUFACTURED IN ACCORDANCE WITH PS 1363-2 BS EN 62368-1	EARTH TERMINAL	Yes
NO. OF USB PORTS 2 NO. OF TYPE-A PORTS 2 USB CHARGING 5V DC 2.4A (shared) Overload and short circuit protection STANDBY POWER 0.1W WARRANTY 2year(s) MANUFACTURED IN ACCORDANCE WITH BS 1363-2 BS EN 62368-1	LOAD/MAX. LOAD	13A
NO. OF TYPE-A PORTS USB CHARGING ADDITIONAL FEATURES STANDBY POWER WARRANTY Overload and short circuit protection 0.1W 2year(s) MANUFACTURED IN ACCORDANCE WITH BS 1363-2 BS EN 62368-1	TERMINAL CAPACITY	2 x 2.5mm² or 1 x 4.0mm²
USB CHARGING ADDITIONAL FEATURES Overload and short circuit protection STANDBY POWER 0.1W WARRANTY 2year(s) MANUFACTURED IN ACCORDANCE WITH BS 1363-2 BS EN 62368-1	NO. OF USB PORTS	2
ADDITIONAL FEATURES Overload and short circuit protection O.1W WARRANTY 2year(s) MANUFACTURED IN ACCORDANCE WITH BS 1363-2 BS EN 62368-1	NO. OF TYPE-A PORTS	2
STANDBY POWER 0.1W WARRANTY 2year(s) MANUFACTURED IN ACCORDANCE WITH BS 1363-2 BS EN 62368-1	USB CHARGING	5V DC 2.4A (shared)
WARRANTY 2year(s) MANUFACTURED IN ACCORDANCE WITH BS 1363-2 BS EN 62368-1	ADDITIONAL FEATURES	Overload and short circuit protection
MANUEACTURED IN ACCORDANCE WITH BS 1363-2 BS EN 62368-1	STANDBY POWER	0.1W
MANUFACTURED IN ACCORDANCE WITH BS 1363-2, BS EN 62368-1	WARRANTY	2year(s)
	MANUFACTURED IN ACCORDANCE WITH	BS 1363-2, BS EN 62368-1
ORIGIN OF MANUFACTURE China	ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE) Yes	DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
	EAN Poto Crostod: 27/02/2025 15:22	5056270808803

Date Created: 27/02/2025 15:33



