

DATASHEET



ENM5C

230V IP20 5W LED Emergency Downlight 5500K
(non-maintained use only)

www.mlaccessories.co.uk

MLA PART CODE	ENM5C
DESCRIPTION	230V IP20 5W LED Emergency Downlight 5500K (non-maintained use only)
NET WEIGHT (KG)	0.55
FINISH	White
DIMENSIONS (MM)	Diameter - 85 Recessed Depth - 60 Minimum Void - 110
CUT-OUT (MM)	Cut-out Diameter - 65
CONSTRUCTION	Construction - Aluminium Construction 2 - & polycarbonate
CLASS	II
IP RATING	IP20
WATTAGE (W)	5
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	460
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	100
LUMENS EMERGENCY MODE (LM)	460
CCT	5500K
LIGHT COLOUR	Daylight
CRI	>70
SVM	0.01
BEAM ANGLE (DEGREES)	60
DIMMABLE	No
EMERGENCY	Non-maintained only
SELF-TEST	No
IC RATED	No
OPERATING TEMPERATURE	25°C
INPUT VOLTAGE	230V 50Hz

CABLE LENGTH (M)	0.35
BATTERY TYPE	LiFePO4
BATTERY INCLUDED	Yes
WARRANTY	3year(s)
WARRANTY INFORMATION	(excluding battery)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270878721

Date Created: 27/02/2025 19:49

