YBN-UA

Recess Base Adaptor

Features

- Allows base and analogue sensor or conventional detector to be flush mounted
- Supplied with fixing brackets
- Colour-matched to existing Ivory and White sensor/detector ranges
- Sturdy construction, easy to install
- Suitable for a maximum ceiling thickness of 30 mm



(shown with base fitted - not included)

Description

Model YBN-UA is a mounting adaptor for both the ESP and CDX Range of sensors and Detectors and their associated mounting bases.

The YBN-UA allows a base and head combination to be flush mounted by providing a recess fixing the ceiling.

It is supplied with a fixing clamp kit (YYA-1) which secures the YBN-UA within a pre-cut hole up to a maximum ceiling thickness of 30mm.

Specification	
Product Code	YBN-UA YBN-UA(WHT)
Operating Temperature Range	-10 °C to + 50 °C
Stroage Temperature Range	-30 °C to + 60 °C
Maximum Humidity	95% (RH) - Non-condensing (at 40 °C)
Colour / Material	Ivory or White / ABS
Weight (g) / Dimensions (mm)	65 / ø 140 x H 44
Height when fitted flush (mm)	7
Drilled hole size (mm)	115
Compatible Bases	All YBN Range, YBO-R/5 Range, YBO-R/6 Range, YBO-R/4 Range
Fixing Centres (mm)	48 ~ 74

For further information visit our website.
Hochiki reserves the right to alter the specification of its products from time to time without notice. Although every effort has been made to ensure the accuracy of the information contained in this document it is not warranted or represented by Hochiki to be a complete and up-to-date description. Check online for current version.