

DS-2CE78U1T-IT3F/GREY 8 MP Turret Camera



Key Features

- 8.29 MP high performance CMOS
- 3840 × 2160 resolution
- 2.8 mm, 3.6 mm, 6 mm, 8 mm, 12 mm fixed lens
- EXIR2.0, smart IR, up to 60 m IR distance
- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)
- IP67
- Up the coax (HIKVISIONC)




Specification



| Camera | |
|-----------------------------------|--|
| Image Sensor | 8.29 megapixel progressive scan CMOS |
| Signal System | PAL/NTSC |
| Frame Rate | TVI: 8MP@12.5fps, 8MP@15fps, 5MP@20fps, 4MP@25fps, 4MP@30fps, 2MP@25fps, 2MP@30fps CVI: 8MP@12.5fps, 8MP@15fps AHD: 8M@12.5fps, 8M@15fps CVBS: 960H P/N |
| Resolution | 3840 (H) × 2160 (V) |
| Min. Illumination | Color: 0.01 Lux@(F1.2, AGC ON), 0 Lux with IR |
| Shutter Time | PAL: 1/12.5 s to 1/50,000 s NTSC: 1/15 s to 1/50,000 s |
| Lens | 2.8 mm, 3.6 mm, 6 mm, 8 mm, 12 mm fixed lens |
| Horizontal Field of View | 102.2° (2.8 mm), 79° (3.6 mm), 50.8° (6 mm) , 37.73° (8 mm), 23.96° (12 mm) |
| Lens Mount | M16 |
| Day & Night | IR cut filter |
| Angle Adjustment (Bracket) | Pan: 0° to 360°, Tilt: 0° to 75°, Rotate: 0° to 360° |
| Synchronization | Internal synchronization |
| DWDR (Digital Wide Dynamic Range) | 105 dB |
| Menu | |
| AGC | Yes |
| Day/Night Mode | Auto/Color/BW (Black and White) |
| White Balance | Auto/Manual |
| BLC (Backlight Compensation) | Yes |
| Language | English |
| Functions | Brightness, Sharpness, DNR, Mirror, Smart IR, HLC |
| Interface | |
| Video Output | 1 HD analog output |
| Switch Button | TVI/AHD/CVI/CVBS |
| General | |
| Operating Conditions | -40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation) |
| Power Supply | 12 VDC±25% <i>*You are recommended to use one power adapter to supply the power for one camera.</i> |
| Power Consumption | Max. 5.3 W |
| Protection Level | IP67 |
| Material | Enclosure: Plastic Main body: Metal |
| IR Range | Up to 60 m |
| Communication | Up the coax, Protocol: HIKVISIONC (TVI output) |
| Dimensions | Ø 109.82 mm × 91.03 mm (Ø 4.32" × 3.6") |
| Weight | Approx. 320 g (0.71 lb.) |

Order Models

DS-2CE78U1T-IT3F

Dimension

Accessory



DS-1272ZJ-110-TRS/GREY
Wall Mount

DS-1280ZJ-S/GREY
Junction Box

Distributed by



HIKVISION®

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Africa
T +27 (10) 0351172
sale.africa@hikvision.com

Hikvision Europe
T +31-23-55-42-770
info.eu@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Oceania
T +61-2-8599-4233
salesau@hikvision.com

Hikvision Hong Kong
T +852-2151-1761

Hikvision Middle East
T +971-4-8816086
salesme@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Canada
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Poland
T +48-22-460-01-50
poland@hikvision.com

Hikvision Korea
T +82-31-731-8841
sales.korea@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision UK
T +01628-902140
support.uk@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com