Video Intercom Network Indoor Station



Key Feature

- 7-inch colorful touch screen with resolution 1024 \times
- Supports Android app installation
- Open platform for the third-party software integration
- Video intercom & live view on mobile phone all-day
- Built-in Hik-Connect for all-in-one management
- Wireless intrusion panel for on-site management
- Receives 7 seconds of video verification from alarm systems

Specification

		Addio quality	Noise supp	
System parameters		Volume		
Operating	Embedded Android operation system	adjustment	Adjustable	
system	Embedded / marold operation system	Capacity		
ROM	2 GB	Event capacity	200	
RAM	8 GB Emmc	Notice capacity	16	
CPU	Embedded processor	Linked indoor		
Display parameters		extensions	5	
Screen size	7-inch	capacity		
Operation	Canaditive touch coreen	Network parame	Network parameters	
method	Capacitive touch screen	Communication		
Туре	Colorful TFT	protocol	TCP/IP, SIP,	
Resolution	1024 × 600	Wired network	Support	
Video parameters		Wi-Fi standard	Wi-Fi 802.:	
Lens	/	Bluetooth		
Resolution	/	version	/	
FOV	/	3G/4G standard	1	
WDR	/	Zigbee	1	
		-		


1
1

Focal length	/			
Audio parameters				
Audio				
compression	G.711 U, G.711 A			
standard				
Audio input	Built-in omnidirectional microphone			
Audio output	Built-in loudspeaker			
Audio				
compression	64 Kbps			
bitrate				
Audio quality	Noise suppression and echo cancellation			
Volume	Adjustable			
adjustment	Adjustable			
Capacity				
Event capacity	200			
Notice capacity	16			

capacity					
Network parameters					
Communication protocol	TCP/IP, SIP, RTSP				
Wired network	Support				
Wi-Fi standard	Wi-Fi 802.11 b/g/n				
Bluetooth version	/				
3G/4G standard	/				
Zigbee	/				

Device interfaces			
Alarm input	8		
Network interface	1 RJ-45 10/100 Mbps self-adaptive		
TAMPER	/		
RS-485	1		
TF card	1		
Alarm output	1 relay output, 1 alarm output		
Power interface	1		
General			
Button	1		
Installation	Surface mounting		
Indicator	1		
Weight	Without package: 419.3 g With package: 694 g		
Protective level	/		
Working temperature	-10 °C to 50 °C (14 °F to 122 °F)		
Working humidity	10% to 90%		
Dimensions	187 mm × 137 mm × 25.7 mm (7.36" × 5.39" × 1.01")		
Battery	/		
Power supply	IEEE802.3af, standard PoE 12 VDC, 1 A		
Application environment	Indoor		
Power consumption	≤ 8 W		
Language	English, French, Portuguese (Brazil), Spanish, Russian, German, Italian, polish, Arabic, Turkish, Vietnamese, Hungarian, Dutch, Romanian, Czech, Bulgarian, Ukrainian, Croatian, Serbian, Greek,		

Norwegian, Danish



No.	Description	No.	Description
1	Screen	7	Debugging
			Port
2	Microphone	8	microUSB
			Interface
3	Unlock	9	Loudspeaker
	Button		
4	Power	10	Reserved
	Supply		
	Interface		
5	Alarm	11	TAMPER
	Terminals		
6	RS-485/Rela	12	Network
	y Interface		Interface

Dimension

