





Function Features

- Monitoring and control doors and windows of the switch states
- 2. when the doors and windows open, Door sensor will send signal to glarm
- 3. Remote control "alarm and disarm"
- 4. Alert when battery low, Low power consumption, strong anti-interference
- 5. External hidden power switch
- 6. Removable installation

Technical Parameters

- 1. Working power: 3.7V rechargeable Li-ion battery
- 2. Power: static: < 50uA; dynamic: < 30mA
- 3. Wireless transmission distance: ≥ 150 meters (open area)
- 4. Service life: ≤ 2 years
- 5. Charging time: 2h charging voltage: 5VDC
- 6. Alarm distance: ≥ 3cm

Installation and use

- The magnet fixed to the door, 1.6 meters above the ground, to prevent child collisions.
- Controlling the launch part of the fixed installation in the door frame, pay attention to maintain the level with the magnet, while the gap should be less than 10 mm.
- When the detector battery is low, the indicator light interval 5S flashing once, at this time must be as soon as possible with standard USB line connection charging operation; regardless of power supply When the switch is closed, the charging operation can be carried out.

Note: when the power switch is on, the indicator light is long and the detection function is normal.

When the power switch is closed: about 10 seconds delay, the indicator light is long, no detection function during the period.

 According to the deployment of key, remote host in defense state (only set "away" mode).

www.ener-j.co.uk info@ener-j.co.uk