



All for better networking.

MW5s

AC1200 Whole Home Mesh WiFi System

www.ener-j.co.uk



MW5s AC1200 Whole Home Mesh WiFi System


Product Description

The Tenda nova MW5s is a whole home mesh WiFi system designed for medium-to-larger sized households that have high speed broadband services coming into your home. Powered by Tenda's proprietary mesh technology, creating a distributed network throughout your home. A 3-pack of the MW5s covers up to 3500 square feet and works well behind multiple walls. The primary node features gigabit ports, getting the most out of your high speed broadband service and ensures smooth streaming of 4K videos. The secondary nodes automatically connect using pre-paired configurations, making setup a breeze. All of these make the Tenda nova MW5s an ideal choice for whole home WiFi coverage.

More features

- * Easy setup: The secondary node automatically connects to the primary node making cabling unnecessary.
- * Parental Controls: Manage your child's online time.
- * Security: Supports access control and guest network.

Selling Points



Works well with high speed broadband

With 2 gigabit ports included, the MW5s gets the most out of your high speed broadband services coming into your home.



Covers up to 3500 square feet

Powered by Tenda's proprietary mesh technology, each node automatically connects to the other, creating a distributed network throughout your entire home. A 3-pack of nova MW5s covers up to3500 square feet Go big and easily expand your WiFi network in the future simply by adding nodes.




Two external power amplifiers for each band to enhance the whole WiFi coverage

Two external power amplifiers used both on 2.4 GHz and 5 GHz bands of the primary node to enhance the signal strength and receiving capability, helpling the nova MW5s outperform ordinary routers.



Built-in dual band antennas for excellent wall penetration capability

With features that optimize both the 2.4 GHz and 5 GHz bands, the nova MW5s system automatically adjusts the data rates when it works behind multiple walls.



RF optimization for excellent wall penetration performance

By optimizing matching circuits and applying Maximal Ratio Combining (MRC) technology, the nova MW5s dramatically improves WiFi transmission, increasing wall penetration and distributing much broader WiFi coverage.

Selling Points



Beamforming technology concentrates the signal for better wall penetration

Powered by Beamforming technology, the nova MW5s projects a stronger WiFi signal in a direction where your devices are located. Instead of just broadcasting signals to a wide area, Tenda's Beamforming concentrates the signal and aims it directly at the target.



Automatic networking makes setup a breeze

All nodes are delivered pre-paired right out of the box, making the system easy to setup and an ideal choice for whole home WiFi coverage.



Supports up to 60 devices

Combining the 1 GHz main chip with MU-MIMO technology, the nova MW5s communicates simultaneously with multiple devic es, ensuring a lag-free internet connection when you enable the Capacity-oriented Mode using the App.

Purchase Guide

Mode Feature	MW2 (3-pack)	MW3 (3-pack)	MW5/MW5s (3-pack)	MW6 (3-pack)	MW12 (3-pack)
WiFi Speed	N450	AC1200	AC1200	AC1200	AC2200
Compatible Broadband	50 Mbps	100 Mbps	>100 Mbps	≥200 Mbps	≥500 Mbps
Coverage Area*	up to 3000 sq.ft	up to 3500 sq.ft	up to 3500 sq.ft	up to 6000 sq.ft	up to 6000 sq.ft
Max. Mesh nodes supported (Qty./Size)	3 (3000 sq.ft)	5 (5000 sq.ft)	6 (6000 sq.ft)	9 (12000 sq.ft)	12 (15000 sq.ft)
Max. No. of Connected Devices	20 devices	40 devices	60 devices	90 devices	120 devices

Specification

Hard	lware S	pecifi	cati	ons

nardware specifications	
Standards	IEEE 802.3, IEEE 802.3u
Ports	Mesh5: 2 x 10/100/1000Mbps Ethernet ports -1 WAN/LAN port -1 LAN port Mesh3f: 2 x 10/100Mbps Ethernet ports -1 WAN/LAN port -1 LAN port
Antennas	Mesh5: 2 x 3 dBi built-in omni-directional antennas Mesh3f: 2 x 3 dBi built-in omni-directional antennas
Button	Mesh5: 1 x Reset button Mesh3f: 1 x Reset button
Power	Mesh5 Input: 100 - 240 V, 50/60 Hz, 0.6 A Output: DC 12 V == 1 A
	Mesh3f Input: 100 - 240V, 50/60 Hz, 0.3 A Output: 9 V 1 A
Indicator	Mesh5: 1 System/Signal Mesh3f: 1 System/Signal
Dimensions	Mesh5: 91 mm x 91 mm x 93 mm (3.58 in. x 3.58 in. x 3.66 in.) Mesh3f: 91 mm x 91 mm x 93 mm (3.58 in. x 3.58 in. x 3.66 in.)
Wireless Features	
Wireless Standards	5GHz: IEEE 802.11ac/a/n
	2.4GHz: IEEE 802.11b/g/n
Data Rate	5 GHz 867 Mbps 2.4 GHz 300 Mbps
Frequency	Simultaneous dual band 2.4 GHz & 5 GHz
Basic Features	SSID Broadcast
	Beamforming MU-MIMO
Wireless Security	WPA/WPA2-PSK
Wireless Roaming	Compliant with IEEE 802.11k/v/r
Software Features	
Internet Connection Type	PPPoE, Dynamic IP, Static IP, Bridge Mode
DHCP Server	DHCP Server
	DHCP Client List
Virtual Server	Port Forwarding
	UPnP

Specification

Firewall	UDP flood attack defense TCP flood attack defense ICMP flood attack defense
DNS	Manually setting up DNS server
VPN	IPsec pass through PPTP pass through L2TP pass through
	Parental Control
Others	Guest Network Firmware upgrade online
	Resetting to factory settings
Setup Requirements	A mobile device running Android 4.0+ or iOS 8+
Others	
Temperature	Operating Temperature: 0 °C - 40 °C
Temperature	Operating Temperature: 0 °C - 40 °C Storage Temperature: -40 °C - 70 °C
Temperature Humidity	Storage Temperature: -40 °C - 70 °C
	Storage Temperature: -40 °C - 70 °C Operating Humidity: (10% - 90%) RH non-condensing
Humidity	Storage Temperature: -40 °C - 70 °C Operating Humidity: (10% - 90%) RH non-condensing Storage Humidity: (5% - 90%) RH non-condensing
Humidity Certificates Package Contents	Storage Temperature: -40 °C - 70 °C Operating Humidity: (10% - 90%) RH non-condensing Storage Humidity: (5% - 90%) RH non-condensing FCC, CE, RoHS, EAC, IC
Humidity Certificates	Storage Temperature: -40 °C - 70 °C Operating Humidity: (10% - 90%) RH non-condensing Storage Humidity: (5% - 90%) RH non-condensing FCC, CE, RoHS, EAC, IC Mesh5 x 1, Mesh3f x 2 12 V/1 A power adapter x 1