



24W LED BULKHEAD CEILING LIGHT with Microwave Sensor & Emergency



SKU Code:
T761 - White

85lm/w
LUMENS

24W
WATTS

IP65

This fitting is a 24W LED bulkhead light fitting ideal for outdoor wall lighting complete with a microwave motion sensor. It has an IP65 rating (it is waterproof) and offers a 4000K light. With a 110mm projection and approx. 280mm diameter, this bulkhead has a polycarbonate base in white, a gloss white trim ring, and an opal diffuser.

This range of LED bulkheads are robust and versatile with an IP65 rating which protects from dust and jets of water. The sensor is an active motion detector: it emits a high frequency electromagnetic wave 5.9Hz and receives its echo. The sensor detects the change in echo from movement in its detection zone. A microprocessor then triggers the switch light ON command.

Emergency Backup Information

- **Input voltage:** 170V-250V
- **Battery capacity:** 1500mAh
- **First Charging Time:** 24 hours
- **Emergency Backup time:** 3H
- **LED voltage:** 72V
- Detection is possible through doors, panels of glass, and thin walls.
- They are ideal for hospitals, nursing homes, schools, and any other commercial or domestic environments, both indoors and outdoors as needed.



Specifications

| | |
|-------------------------------|--------------------------------|
| Wattage | 24W |
| Housing Material | ABS |
| Housing Colour | White |
| CCT | 4000K |
| Input Voltage | 170V-250V, 50/60 Hz |
| Product Measurement | Ø280*63mm |
| RA | 80 |
| PF | >0.5 |
| Dimmable | No |
| Power Supply | Internal CE standard IC Driver |
| Lumens Per Watt | 85 |
| Luminous flux | 2040 lm |
| Beam | 180 |
| IP Rating | IP65 |
| IK Rating | IK10 |
| Suitable temperature | -20~+45 |
| Switching cycles | ≥15000 |
| Starting time (Seconds) | <15 |
| Energy efficiency class | A+ |
| Microwave Sensor | Inbuilt Microwave Sensor |
| Static Power Dissipation | <0.5W |
| Microwave Frequencies | 5.8 GHz +/- 75 MHz |
| Microwave Power | <0.2 mW |
| Detection Range | (Diameter x Height): 10m x 6m |
| Detection Angle | 30 ~ 150 |
| Installation Height | 6m |
| Accessories | Surface Mounting Kit Included |
| Quick Connector | Included |
| Colour Box Dimension | 290*75*390mm |
| Product Weight with Colourbox | 1.100 Kgs |
| Pcs per Master Carton | 12 pcs |
| Master Carton Dimension | 0.6X0.48X0.31CM |
| Master Carton Weight | 18Kgs |
| Lifetime | 30000 hours |