

Single Way Video Door Entry

Product Code: APDSSW

Description: Singleway Video Door Station



General Information

Dimensions (mm)	165 x 85 x 53
Materials	ABS
Mounting	Surface Mounting
Weight (Kg)	.39
Warranty (Years)	3

Media Information

Illumination	5 White light LEDs
Sensitivity (Lux)	0.1
Sensor Size (")	1/3
Lens size (mm)	3.6
Audio	Full Duplex

Environment

Ingress Protection	IP55
Operating Temperature (°C)	-20 to +40

Supplied Fixing Screws, and Wall Plugs, User Manual

Accessories EVBPSBB: 12V Lock power supply with battery backup
 APPOWSWDR: Din Mounted BUS power supply
 APMONW: Aperta BUS Monitor in white
 APMONB: Aperta BUS Monitor in Black
 APMONWG: Aperta GUI BUS Monitor in white
 APMONBG: Aperta GUI BUS Monitor in Black
 APAUDH: Aperta BUS Audio Only Handset in White
 APAUDHBLK: Aperta BUS Audio Only Handset in Black
 ENTERD: Flush Electric Lock
 ENTERD-YLR: Surface Electric Lock

Supply & Power

Operating Voltage (V AC)	
Operating Voltage (V DC)	24 (BUS)
Global Selections	Normally Open or Normally Closed; Volt-Free or 12V DC300mA
Effective Distance to PowerSupply (M)	50
Lock outputs	2

Network

Recommended BUS Cable	Cat5e or higher
Communication Protocol	BUS

Features

Outdoor Station rings so that the user knows whether the call has been answered, calls last up to 30 seconds

Accessories

EVBPSBB: 12V Lock power supply with battery backup
 APPOWSWDR: Din Mounted BUS power supply
 APMONW: Aperta BUS Monitor in white
 APMONB: Aperta BUS Monitor in Black
 APMONWG: Aperta GUI BUS Monitor in white
 APMONBG: Aperta GUI BUS Monitor in Black
 APAUDH: Aperta BUS Audio Only Handset in White
 APAUDHBLK: Aperta BUS Audio Only Handset in Black
 ENTERD: Flush Electric Lock
 ENTERD-YLR: Surface Electric Lock

Additional Information Simple 2-core Installation
 High-Resolution Colour Camera

