


## **Technical Specification**

## ESP. Scolmore GROUP

## Video Door Entry Monitor

Product Code: APMONW Description: Colour Video Door Entry Monitor



General Information		Supply & Power	
Dimensions (n	nm) 152 x 215 x 18	Operating Voltage (V	AC)
Fir	nish White	Operating Voltage (V	<b>DC)</b> 24 (BUS)
Mater	ials ABS	Effective Distance to PowerSupply	<b>(M)</b> 100
Mount	ting Surface	Master/S	Slave Yes (set by 6th DIP Switch)
Weight (	<b>Kg)</b> .45	Network	
Warranty (Yea	ars) 3	Recommended BUS Cable	Cat5e or higher
Media Information		Communication Protocol	BUS
Illumination	Backlight Screen and Buttons		
Audio	Full Duplex		
Adjustments	Volume, Brightness, and Contrast D	ials	
Programming			
User Interaction	4 buttons		
Programming Type	7 x DIP switches		
Maximum Settable Address	32 (set by first 5 DIP Switches)		
Environment			
Ingress Protection	IP20	<del></del>	
Operating Temperature (°C)	0 to +40		

Supplied Fixing Screws, and Wall Plugs, Surface Mount Bracket, User Manual

Accessories APPOWSWDR: Aperta Singleway BUS power supply APDSSW: Aperta BUS Single Way Door Station

APDSSWKP: Aperta BUS Single Way Door Station With Keypad

 Features
 Accessories

 Internal Call Facility
 APPOWSWDR: Aperta Singleway BUS power supply

APDSSW: Aperta BUS Single Way Door Station APDSSWKP: Aperta BUS Single Way Door Station With Keypad

Additional Information Simple 2-core Installation

For use with both Single way & Multiway Applications

