

**Product Code:** ECSPK4

**Description:** Smart Security Alarm Kit with Hub, 4x PIRs, 2x Door Contacts and 2x Remote Fobs



**Component 1**

ECSPHB - Smart Alarm Hub with Battery Backup

**Quantity**

1

**Component 2**

ECSPPIR - Smart Security PIR

**Quantity**

4

**General Information**

Dimensions (mm)	109.5 x 109.5 x 40
Finish	White
Materials	ABS
Mounting	Surface
Available Operations	Home/Arm/Disarm/SOS
Sounder Output (dB)	95
Maximum Devices	32
Transmission frequency (MHz)	433
Weight (Kg)	0.25

**Supply & Power**

Operating Voltage (V DC)	12
Power Consumption (A)	1
Battery Specification	7.4V 600mAh Lithium Polymer
Power Reserve	8 Hours (Approx.)

**Transmission**

Router Transmission Frequency (GHz)	2.4 (IEEE 802.11 b/g/n)
Router Transmission Range (m)	150

**Auxiliary**

GSM	Yes (Full-size SIM Card)
GSM Frequency (MHz)	850, 900, 1800 & 1900

**Environment**

Operating Temperature (°C)	-10 to 55
Relative Humidity Resistance (%)	<80 (non-condensing)

**General Information**

Dimensions (mm)	107 x 53 x 32
Bracket Dimensions (mm)	52 x 30 x 26.5
Finish	White
Mounting	Surface
PIR Range (m)	8
Number of PIRs	1
Transmission frequency (MHz)	433
Operating Voltage (V DC)	3
Power Consumption (A)	0.0095
Battery Type	AA (LR06) x 3
Power Reserve	12 Months (Approx.)
Zone Types	Normal Sensor/24h mode/Delay mode/ Home mode/24h mute sensor/Home delay mode
Operating Temperature (°C)	-10 to 55
Relative Humidity Resistance (%)	<80 (non-condensing)
Weight (Kg)	0.046

**Product Code:** ECSPK4

**Description:** Smart Security Alarm Kit with Hub, 4x PIRs, 2x Door Contacts and 2x Remote Fobs

**Component 3**  
ECSPCT - Smart Door / Window Contact Sensor **Quantity** 2

General Information	
Dimensions (mm)	55.7 x 30.3 x 16
Finish	White
Materials	ABS
Mounting	Surface
Magnet Dimensions (mm)	25 x 10 x 9
Transmission frequency (MHz)	433
Operating Voltage (V DC)	3
Power Consumption (A)	0.015
Battery Type	CR2477
Power Reserve	12 Months (Approx.)
Zone Types	Normal Sensor/24h mode/Delay mode/Home mode/24h mute sensor/Home delay mode
Operating Temperature (°C)	-10 to 55
Relative Humidity Resistance (%)	<80 (non-condensing)
Weight (Kg)	0.2

**Warranty Years** 1

**Supplied** Fort Hub  
Fort PIR x 4  
Fort Door/Window Contact x 2  
Fort Remote Control x 2  
AC Adapter  
Product Batteries  
Mounting Screws & Wall plugs  
User Guides

**Component 4**  
ECSPRC - Smart Alarm Remote Control **Quantity** 2

General Information	
Dimensions (mm)	57 x 31 x 11
Finish	Black
Materials	ABS
Available Operations	Home/Arm/Disarm/SOS
Transmission frequency (MHz)	433
Operating Voltage (V DC)	3
Battery Type	CR 2025
Power Consumption (mA)	<7
Power Reserve	12 Months (Approx.)
Operating Temperature (°C)	-10 to 55
Relative Humidity Resistance (%)	<80 (non-condensing)
Weight (Kg)	0.02

