

## **Technical Specification**



2

**Product Code: ECSPK6** 

**Description:** Smart Security Alarm Kit with Hub, 2x Pet PIRs, 2x Door Contacts and 2x

Remote Fobs



Component 1 Quantity

ECSPHB - Smart Alarm Hub with Battery Backup

**Component 2** Quantity ECSPPET - Smart Security Pet PIR

General Information				
Dimensions (mm)		109.5 x 109.5 x 40		
Finish		White		
Materials		ABS		
Mounting		Surface		
Available Operations		Home/Arm/Disarm/SOS		
Sounder Output (dB)		95		
Maximum Devices		32		
Transmission frequency (	MHz) 4	433		
Weight (Kg) 0		0.25		
Supply & Power				
Operating Voltage (V DC)		12		
Power Consumption (A)		1		
Battery Specification		7.4V 600mAh Lithium Polymer		
Power Reserve		8 Hours (Approx.)		
Transmission				
Router Transmission Frequency (GHz)		2.4 (IEEE 802.11 b/g/n)		
Router Transmission Range (m)		150		
Auxillary				
GSM	Yes (Fu	ıll-size SIM Card)		
GSM Frequency (MHz)	850, 900, 1800 & 1900			
Environment				
Operating Temperature (°C)		-10 to 55		
Relative Humidity Resistance (%) <80 (non-condensing)				

General Information			
Dimensions (mm)	107 x 53 x 32		
Bracket Dimensions (mm)	52 x 30 x 26.5		
Finish	White		
Mounting	Surface		
PIR Range (m)	8		
Number of PIRs	2		
Transmission frequency (MHz)	433		
Minimum Detectable Object	>25		
Weight (Kg)			
Operating Voltage (V DC)	3		
Power Consumption (A)	0.0095		
Battery Type	AA (LR06) x 3		
Power Reserve	12 Months (Approx.)		
Zone Types	Normal Sensor/24h mode/Delay mode/ Home mode/24h mute sensor/Home delay mode		
Operating Temperature (°C)	-10 to 55		
Relative Humidity Resistance (%)	<80 (non-condensing)		
Weight (Kg)	0.046		





## **Technical Specification**



**Product Code: ECSPK6** 

**Description:** Smart Security Alarm Kit with Hub, 2x Pet PIRs, 2x Door Contacts and 2x

Remote Fobs

Quantity Quantity **Component 3** Component 4

ECSPCT - Smart Door / Window Contact Sensor ECSPRC - Smart Alarm Remote Control

General Information		General Information	
Dimensions (mm)	55.7 x 30.3 x 16	Dimensions (mm)	57 x 31 x 11
Finish	White	Finish	Black
Materials	ABS	Materials	ABS
Mounting	Surface	Available Operations	Home/Arm/Disarm/SOS
Magnet Dimensions (mm)	25 x 10 x 9	Transmission frequency (MHz)	433
Transmission frequency (MHz)	433	Operating Voltage (V DC)	3
Operating Voltage (V DC)	3	Battery Type	CR 2025
Power Consumption (A)	0.015	Power Consumption (mA)	<7
Battery Type	CR2477	Power Reserve	12 Months (Approx.)
Power Reserve	12 Months (Approx.)	Operating Temperature (°C)	-10 to 55
,,	Normal Sensor/24h mode/Delay mode/Home mode/24h mute sensor/ Home delay mode	Relative Humidity Resistance (%)	<80 (non-condensing)
		Weight (Kg)	0.02
Operating Temperature (°C)	-10 to 55		
Relative Humidity Resistance (%)	<80 (non-condensing)		

Warranty Years 1

Supplied Fort Hub

Fort Pet PIR x 2

Weight (Kg) 0.2

Fort Door/Window Contact x 2 Fort Remote Control x 2 AC Adapter Product Batteries

Mounting Screws & Wall plugs

User Guides

