



Component 1

EVTR - Push Button 'Trades'

Quantity

1

Component 2

71111 - Standard 1 Module 1 Channel, 7 Day, 46 Operations

Quantity

1

General Information

| | |
|---------------------------------------|-------------------------------|
| Dimensions (mm) | 85.5 x 85.5 x 43.5 |
| Finish | Silver |
| Materials | Stainless Steel |
| Mounting | Surface Only |
| Weight (Kg) | 0.315 |
| Supply & Power | |
| Maximum Cable Size (mm ²) | 2.5 |
| Operational Life | 100000 |
| Contact Type | SPDT |
| Operation Type | Mechanical Retractable Switch |
| Total Switch Rating | 30A (@250V AC) |
| Environment | |
| Ingress Protection | IP66 |
| Operating Temperature (°C) | -20 to +70 |

General Information

| | |
|--|--|
| Dimensions (mm) | 90 x 17.8 x 63 |
| Materials | Self-Extinguishing Thermoplastic |
| Mounting | Surface Mounting or DIN |
| Available Operations | 46 Operations |
| Display | LCD Display |
| Time Base | Quartz Crystal |
| Quartz Crystal Accuracy (at 20°C) | ≤ ± 0.5 Seconds / Day |
| Distribution Board Mounting | 35mm DIN-rail (DIN EN 60715) |
| Supply Voltage (V AC) | 230 |
| Cable Size (mm ²) | 0.5 - 2.5 |
| Power Consumption (W) | 0.2-1 |
| Battery Type | Replaceable CR2032 |
| Contact Type | SPDT |
| Total Switch Rating | 230V AC, 16A @ 1.0pf |
| Output Contact Type | SPDT |
| Power Reserve @ 20°C | 10 Years (Approx.) |
| IEC Protection Class | Class II When Installed According to Regulations |
| Programming Schedule | 24 Hour, and 7 Day Programmable |
| Switching Modes | ON, OFF, Pulse |
| Summer/Winter Time Change | Yes (Automatic) |
| Program Security | Unlimited (E2-PROM) |
| Pulse length - Pulse function (switching time) | 00:01 up to 59.59 mm:ss |
| Pulse length - Timer (man. switching) | 0:00:01 up to 9:59:59 h:mm:ss |
| Maximum LED Lamp Load Rating (W) | 50 @ 230V |
| Contact Material | AgSnO ² |
| Maximum Incandescent, Halogen Lamp Load Rating (W) | 400 |
| Maximum Compact Fluorescent Lamp Load Rating (W) | 50 |
| Maximum Starting Current (A) | 30 |
| Maximum Fluorescent Lamp with Electronic Ballast Load Rating (W) | 100 |
| Maximum Fluorescent Lamp with Conventional Ballast Load Rating (W) | 100 |
| Minimum Switching power (mW) | 300 (10V/10mA) |
| Ingress Protection | IP20 |
| Operating Temperature (°C) | -30 to +55 |

