

## **Technical Specification**

Product Code: HDVIP132R16TB

**Description:** HDview IP PoE 5MP 32CH NVR 16TB





General Information  Dimensions (mm) 380	Recor	Maximum Capacity	16 Torobytos
Warranty (Years) 3	( 340 X 50	Maximum Capacity	8 Terabytes per SATA connection
		Storage Type	SATA Hard Disk Drive
Supply & Power		Internal HDD	
Operating Voltage (V AC) 110 - 240		SATA Connection(s)	
Power Consumption (mA) <12W		( )	8MP, 5MP, 3MP, 1080p, 720p
Inputs & Outputs			Manual, Schedule, Alarm
Alarm Inputs 16		Environment	
Alarm Outputs 1		Operating Temperature	(°C) 10 to 150
Video Input Channels 32:		Operating temperature	<b>(C)</b>   -10 to +50
16 (F	,		
	igital)		
Audio Output Channels (RCA) 1			
Media Information			
Frames Per Second (FPS)	,		
Display Video Output	,		
	1, 4, 6, 8, 9, 10, 10-1, 12, 13, 13-1, 14, 16, 17, 19, 20, 22, 25, 32 & 36		
Display Resolutions	HDMI 1 (Full GUI): 1024x768, 1280x720, 1280x1024, 1440x900, 1920x1080, 3840x2160/EDID		
	HDMI 2 (Limited GUI): 1024x768, 1280x72		
Cyna Dlaybaak	VGA (Full GUI): 1024x768, 1280x720, 128	JX1024, 1440X900, 1920	)X 1080
	Maximum 16 Channels  Network USB2.0 (Up to 32GB Storage Medium Supported)		
·	Yes (Via Password Reset)		
	ies (via rassword neset)		
Network			
Interface			
	1 x USB 2.0 (Front), 1 x USB 3.0		
	1 x USB 2.0 (Rear) 1 x RS485		
Network Connection	RJ45; 10/100 BASE-T		
	Mobile app, Windows & Mac Client, Web Interface		
Treathern morniorning			
Supplied 1 x USB Mous	e (0.5m), 1 x C13 IEC Cable (0.5m), 1 x Eth	nernet Cable (0.5m)	
Compatible Products HDVIPC: Ran			
REKIP: Range	or Carrieras 5" LED CCTV Monitor		
	5" LED CCTV Monitor 3" LED CCTV Monitor		
	.5" LED GCTV Monitor		

Accessories Feature

**Additional Information** Playback Function: Fast Forward & Reverse (2x, 4x, 8x, 16x) Slow Forward (1/2x, 1/4x, 1/8x, 1/16x)

HDVIP1632RRMB: Rack Mount Bracket IPIN1POE: 1 Channel POE Injector IPSW4POE: 4 Channel POE Switch IPSW8POE: 8 Channel POE Switch



