

Product Code: HDVIP11FDW

Description: 1.1mm Fisheye Lens IP Dome Camera - White



General Information		Recording	
Dimensions (mm)	Ø120 x 55	Storage Type	Micro SD Card
Finish	White	eSATA Connection	RJ45 10M/100M Ethernet, 2.1 x 5.5mm DC Socket
Weight (Kg)	0.4	Environment	
Warranty (Years)	3	Ingress Protection	IP66
Supply & Power		Operating Temperature (°C)	-30 to +55
Operating Voltage (V DC)	12	Storage Temperature (°C)	-30 to +60
Power Consumption (W)	≤ 5		
Other Power Sources	PoE (802.11af)		
Media Information			
B&W Minimum Illumination (Lux)	0.1		
Effective Pixels	5MP (2160 x 2160)		
Sensor Size (")	1/2.9"		
Lens size (mm)	1.1		
Lens Type	Fixed		
Viewing Angle (°)	360		
Auto Electronic Shutter (s)	1/5 - 1/20000		
Alarm	I/O		
Maximum IR Distance (m)	5		
Video Out	CVBS		
Audio	Microphone		
Network			
Communication Protocol	ONVIF		
Interface	RJ45 10M/100M Ethernet, 2.1 x 5.5mm DC Socket		
ONVIF Compliant	Yes		
Network Functions	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, PPPoE, SMTP, NTP, UPnP, SNMP, HTTPS, FTP		
Network Monitoring	Web browser, Client Software, Android & IOS		

Compatible Products Compatible with HDVIP16R & HDVIP32R

Accessories

- IPIN1POE: 1 Channel POE Injector
- IPSW4POE: 4 Channel POE Switch
- IPSW8POE: 8 Channel POE Switch
- IPX100POE: 100m PoE Extender
- CABIP10 : 10 Metre CAT-5e External Use Data Cable
- CABIP20: 20 Metre CAT-5e External Use Data Cable
- CABIP40: 40 Metre CAT-5e External Use Data Cable
- CABIP80: 80 Metre CAT-5e External Use Data Cable
- Compatible with the range of HDView IP Network Video Recorders (NVRs)

