

Product Code: HDVIPC28FDW2

Description: 2.8mm Fixed Lens IP Dome Camera - White



General Information		Recording	
Dimensions (mm)	100x100x82	eSATA Connection	RJ45 10M/100M Ethernet, 2.1 x 5.5mm DC Socket
Finish	White	Environment	
Materials	Powdercoated Aluminium	Ingress Protection	IP66
Mounting	Surface	Operating Temperature (°C)	-30 to +60
Weight (Kg)	0.25	Relative Humidity Resistance (%)	<95 (non-condensing)
Warranty (Years)	3	Supply & Power	
Supply & Power		Operating Voltage (V DC)	12
Power Consumption (W)	<9	Power Consumption (W)	<9
Other Power Sources	PoE (IEEE802.3af)	Media Information	
Media Information		B&W Minimum Illumination (Lux)	0 (@ IR 'ON')
Colour Minimum Illumination (Lux)	0.05 (@ F1.2(AGC 'ON'))	Effective Pixels	5MP (2592 X 1944)
Video Resolution	5MP (2592 x 1944)	Sensor Size (")	1/2.7"
Lens size (mm)	2.8	Lens Type	Fixed
Viewing Angle (°)	97	Auto Electronic Shutter (s)	1/5 - 1/20000
Scanning System	Progressive CMOS	Frames Per Second (FPS)	20 (@5MP)
Baud Rate (bps)	8Kbps – 8Mbps	Maximum IR Distance (m)	30
Auto Gain Control	Auto	Audio	Microphone
Network		Communication Protocol	ONVIF
Interface	RJ45 10M/100M Ethernet, 2.1 x 5.5mm DC Socket	ONVIF Compliant	Yes
Network Functions	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP, UPnP, SNMP, HTTPS, FTP	Network Monitoring	Web browser, Client Software, Android & IOS

- Accessories**
- IPCDBW: IPC Deep Base - White
 - IPIN1POE: 1 Channel POE Injector
 - IPSW4POE: 4 Channel POE Switch
 - IPSW8POE: 8 Channel POE Switch
 - CABIP10 : 10 Metre CAT-5e External Use Data Cable
 - CABIP20: 20 Metre CAT-5e External Use Data Cable
 - CABIP40: 40 Metre CAT-5e External Use Data Cable
 - CABIP80: 80 Metre CAT-5e External Use Data Cable
 - Compatible with the range of HDView IP Network Video Recorders (NVRs)

