

Product Code: MAGPRO-HSD1

Description: Addressable Combined Smoke And Heat Detector



General Information

Dimensions (mm)	ø103 x 42
Finish	White
Materials	ABS
Class	A1R
Available Sensitivity (Selected from CIE)	High/Normal/Middle/Low
Weight (Kg)	0.125
Warranty (Years)	3

Supply & Power

Operating Voltage (V DC)	15 - 30
Nominal Operating Voltage (V DC)	27
Consumption in quiescent state, no communication (µA)	< 160 (@27V DC)
Consumption in quiescent state, with communication (µA)	< 200µA (@27V DC)
Consumption in alarm state, with communication (mA)	6.5
Maximum Output in alarm state at terminal RI (mA)	7.5 (7.5V)

Inputs & Outputs

Maximum Output in alarm state at terminal RI (mA)	7.5 (7.5V)
--	------------

Communication

Protocol Type	Custom (Closed)
----------------------	-----------------

Environment

Ingress Protection	IP30
Operating Temperature (°C)	-10 to +60
Relative Humidity Resistance (%)	93 (±3) (@40°C)

Compatible Products Compatible with MAGPRO-DB, MAGPRO-DBS and MAGPRO-DBSS

Standards BS EN 54-5, BS EN 54-7

Accessories

- MAGPRO-DB: Detector Base
- MAGPRO-DBS: Detector Base with Sounder
- MAGPRO-DBS: Detector Base with Combined Sounder Strobe

