

**Product Code:** PPSPF247

**Description:** Powersaver Plus Electronic 24/7 Fused Boost controller with Programmable Operations



### General Information

Dimensions (mm)	86 x 86 x 35
Depth Without Back Box (mm)	12
Flush Mounting Back Box Depth (mm)	25
Finish	White Gloss
Display	LCD, Clear Indication Display
Materials	ABS
Mounting	Surface and Flush Mounting
Warranty (Years)	3

### Programming

Programming Schedule	24 Hour, 5/2 Day & 7 Day
Available Operations	Up to 10 per Day
Summer/Winter Time Change	Yes (Automatic)
Memory Reserve	Permanent Reserve Setting
Button Lock	Yes
Selectable Boost Durations	15 Minutes, 30 Minutes, 1 Hour, 2 Hours, 4 Hours, or 6 Hours

### Supply & Power

Supply Voltage (V AC)	230
Frequency (Hz)	50
Fuse Fitted (BS1362)	13A
Maximum Cable Size (mm <sup>2</sup> )	2.5 (Flex), 4.0 (Fixed)
IEC Protection Class	Class II

### Environment

Ingress Protection	IP20
Operating Temperature (°C)	0 to +40
Temperature Rating	T40

**Supplied** BS1362 13A Fuse

### Outputs

Number of Outputs	1
Switched Output	230V AC, DPST
Maximum LED Lamp Load Rating (W)	200 @ 230V
Maximum Incandescent, Halogen Lamp Load Rating (W)	750
Maximum Fluorescent Lamp Load Rating (W)	500
Maximum Compact Fluorescent Lamp Load Rating (W)	100
Maximum Fluorescent Lamp Load Rating (W)	500

### Accessories

PSPFUSE - Powersaver Plus Spare Fuses

