

Technical Specification



Product Code: PSPSF24S

Description:

1: Powersaver Plus Electronic 24 Hour Fused Boost controller with Programmable Operations in Silver



General Information		Outputs	
Dimensions (mm)	86 x 86 x 35	Number of Outputs	1
Depth Without Back Box (mm)	12	Switched Output	240V AC, DPST
Flush Mounting Back Box Depth (mm)	25	Maximum LED Lamp Load Rating (W)	200 @ 230V
Finish	Silver	Maximum Incandescent, Halogen	750
Display	LCD, Clear Indication Display	Lamp Load Rating (W)	
Materials	ABS	Maximum Fluorescent Lamp Load	500
Mounting	Surface and Flush Mounting	Rating (W)	
Warranty (Years)	3	Maximum Compact Fluorescent Lamp Load Rating (W)	100
Programming		- Maximum Fluorescent Lamp Load	500
Programming Schedule 24 Hour		Rating (W)	300
Available Operations Up to 10 per Day			
Summer/Winter Time Change Yes (Automatic)			
Memory Reserve Permanent Reserve Setting			
Button Lock Yes			
	15 Minutes, 30 Minutes, 1 Hour, 2 Hours, 4 Hours, or 6 Hours		
Supply & Power	, ,		
Supply Voltage (V AC)	230	-	
Frequency (Hz)	50		
Fuse Fitted (BS1362)	13A		
Maximum Cable Size (mm ²)	2.5 (Flex), 4.0 (Fixed)		
IEC Protection Class	Class II		
Environment			
Ingress Protection	20	-	
Operating Temperature (°C) 0	to +40		
Temperature Rating	40		
Supplied BS1362	13A Fuse		

Accessories

PSPFUSE - Powersaver Plus Spare Fuses

Unit 7 Target Park, Shawbank Road, Lakeside, Redditch B98 8YN United Kingdom **T:** +44 (0)1527 515150 | **F:** +44 (0)1527 515143 **E:** info@espuk.com | **W:** espuk.com



Page 1 of 1 (18/10/22) Errors & Omissions excluded. Specification is subject to change without notice.